

TRANCE ADVANCED E+ SE



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 4, 120 Nm, 48 V, 850 W peak power
BEDIENINGSUNIT	Giant RideControl Ergo 5 wireless, Integrated E+ System & seatpost remote
DISPLAY	Giant RideControl Go Lux
ACCU	Giant EnergyPak Smart 840, 48V
LADER	Giant Smart Charger X, 48 V 4A
FRAME	
FRAME	Advanced-grade composite frame, Advanced Forged Composite upper rocker, 150mm Maestro suspension system, 3-position flip chip adjustable geometry, 148 mm BOOST hub spacing, ZS66/ZS66 headset compatible
VOORVORK	CREST TR Elite E-tuned, 160mm, Dual Air, Elite damper
DEMPER	CREST Flotrac TR E-tuned, 185 x 55 mm, custom tuned, recommended sag 30%
ONDERDELEN	
STUUR	Giant Contact SL Trail Integrated, 27mm rise, Up: 5° Back: 8°, 800mm
HANDVATTEN	Giant Tactal Pro
STUURPEN	Giant Contact SL Trail Integrated, 40 mm
ZADELPEN	Giant Contact Switch E+, 30.9 mm, electronic dropper post
ZADEL	Giant Romero HD
AFMONTAGE	
SHIFTERS	Giant RideControl Ergo 5 wireless
ACHTERDERAILLEUR	TRP Electronic RD, 10/11/12-speed compatible, TRD-002
REMMEN	TRP EVO Comp, hydraulic disc, 4-piston, 220 mm [F] 203 mm [R]
REMHENDELS	TRP EVO Comp
CASSETTE	Shimano LinkGlide, 11-speed, 11-50T
AANDRIJVING	KMC eGlide, high-torque e-bike optimized chain 11-speed
CRANKSET	Praxis Type-2 alloy, 155 mm

WIELSET	
VELGEN	Giant TRA HD, alloy, 30 mm inner width, Wide Guard Technology
NAVEN	Giant TRA HD, E-Drive, titanium ratchet system, 72T engagement, 15 x 110 mm [F] 12 x 148 mm [R], e-bike optimized
SPAKEN	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
BANDEN	Maxxis Assegai 29 X 2.50-inch Foldable, TLR, EXO+, 3C MaxxGrip [F], Maxxis Minion DHR II 27.5 x 2.4-inch Foldable, TLR, EXO+, MaxxTerra [R]
EXTRA'S	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
VERLICHTING	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

Adviesprijs: € 6.499,00

GEOMETRIE

FRAME	S			M			L			XL		
	LOW HIGH			LOW HIGH			LOW HIGH			LOW HIGH		
Zitbuis Hoek	76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6° 77,0° 77,4°			76,6° 77,0° 77,4°		
Frame Lengte (horizontaal) (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Balhoofdbuis Lengte (mm)	110			120			130			140		
Balhoofdbuis Hoek	64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1° 64,5° 64,9°			64,1° 64,5° 64,9°		
Wielbasis (mm)	1200 1199 1197			1239 1237 1236			1267 1265 1264			1300 1299 1298		
Liggende achtervork lengte (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Stack (mm)	634	631	629	643	640	638	652	649	647	661	659	656
Reach (mm)	422	425	428	457	460	463	477	480	484	504	510	513
Cranklengte (mm)	155			155			155			155		

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.