

TRANCE ADVANCED E+ SE



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro 4, 120 Nm, 48 V, 850 W peak power
BEDIENINGSUNIT	Giant RideControl Ergo 5 wireless, Integrated E+ System & seatpost remote
DISPLAY	Giant RideControl Go Lux
ACCU	Giant EnergyPak Smart 840, 48V
LADER	Giant Smart Charger X, 48 V 4A
FRAME	
FRAME	Advanced-grade composite frame, Advanced Forged Composite upper rocker, 150mm Maestro suspension system, 3-position flip chip adjustable geometry, 148 mm BOOST hub spacing, ZS66/ZS66 headset compatible
VOORVORK	CREST TR Elite E-tuned, 160mm, Dual Air, Elite damper
DEMPER	CREST Flotrac TR E-tuned, 185 x 55 mm, custom tuned, recommended sag 30%
ONDERDELEN	
STUUR	Giant Contact SL Trail Integrated, 27mm rise, Up: 5° Back: 8°, 800mm
HANDVATTEN	Giant Tactal Pro
STUURPEN	Giant Contact SL Trail Integrated, 40 mm
ZADELPEN	Giant Contact Switch E+, 30.9 mm, electronic dropper post
ZADEL	Giant Romero HD
AFMONTAGE	
SHIFTERS	Giant RideControl Ergo 5 wireless
ACHTERDERAILLEUR	TRP Electronic RD, 10/11/12-speed compatible, TRD-002
REMMEN	TRP EVO Comp, hydraulic disc, 4-piston, 220 mm [F] 203 mm [R]
REMHENDELS	TRP EVO Comp
CASSETTE	Shimano LinkGlide, 11-speed, 11-50T
AANDRIJVING	KMC eGlide, high-torque e-bike optimized chain 11-speed
CRANKSET	Praxis Type-2 alloy, 155 mm

WIELSET	
VELGEN	Giant TRA HD, alloy, 30 mm inner width, Wide Guard Technology
NAVEN	Giant TRA HD, E-Drive, titanium ratchet system, 72T engagement, 15 x 110 mm [F] 12 x 148 mm [R], e-bike optimized
SPAKEN	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
BANDEN	Maxxis Assegai 29 X 2.50-inch Foldable, TLR, EXO+, 3C MaxxGrip [F], Maxxis Minion DHR II 27.5 x 2.4-inch Foldable, TLR, EXO+, MaxxTerra [R]
EXTRA'S	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
VERLICHTING	Optional: Giant Recon series e-bike lights available and direct-connect compatible
LIMITS	
COMBINED MAXIMUM LOAD LIMIT	156kg

Adviesprijs: € 6.499,00

GEOMETRIE

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Zitbuis hoek	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°	76,6° 77,0° 77,4°
Frame Lengte (horizontaal) (mm)	568 567 566	605 604 603	630 629 628	662 661 660
Balhoofdbuis Lengte (mm)	110	120	130	140
Balhoofdbuis Hoek	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°	64,1° 64,5° 64,9°
Wielbasis (mm)	1200 1199 1197	1239 1237 1236	1267 1265 1264	1300 1299 1298
Liggende achtervork lengte (mm)	443 443 443	443 443 443	443 443 443	443 443 443
Stack (mm)	634 631 629	643 640 638	652 649 647	661 659 656
Reach (mm)	422 425 428	457 460 463	477 480 484	504 510 513
Cranklengte (mm)	155	155	155	155

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.