

TRANCE ADVANCED E+ SE



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Pro 4, 120 Nm, 48 V, 850 W peak power
KONTROLLER	Giant RideControl Ergo 5 wireless, Integrated E+ System & seatpost remote
VISA	Giant RideControl Go Lux
BATTERI	Giant EnergyPak Smart 840, 48V
LADDARE	Giant Smart Charger X, 48 V 4A
RAM	
RAM	Advanced-grade composite frame, Advanced Forged Composite upper rocker, 150mm Maestro suspension system, 3-position flip chip adjustable geometry, 148 mm BOOST hub spacing, ZS66/ZS66 headset compatible
GAFFEL	CREST TR Elite E-tuned, 160mm, Dual Air, Elite damper
BAKDÄMPARE	CREST Flotrac TR E-tuned, 185 x 55 mm, custom tuned, recommended sag 30%
KOMPONENTER	
STYRE	Giant Contact SL Trail integrated, 27mm rise, Up: 5° Back: 8°, 800mm
GREPPAR	Giant Tactal Pro
STAM	Giant Contact SL Trail Integrated, 40 mm
SADELSTOLPE	Giant Contact Switch E+, 30.9 mm, electronic dropper post
SADEL	Giant Romero HD
DRIVLINA	
VÄXLAR	Giant RideControl Ergo 5 wireless
BAKVÄXEL	TRP Electronic RD, 10/11/12-speed compatible, TRD-002
BROMSAR	TRP EVO Comp, hydraulic disc, 4-piston, 220 mm [F] 203 mm [R]
BROMSSPAKAR	TRP EVO Comp
KASSETT	Shimano LinkGlide, 11-speed, 11-50T
KEDJA	KMC eGlide, high-torque e-bike optimized chain 11-speed
VEVPARTI	Praxis Type-2 alloy, 155 mm

HJUL	
FÄLGAR	Giant TRA HD, alloy, 30 mm inner width, Wide Guard Technology
NAV	Giant TRA HD, E-Drive, titanium ratchet system, 72T engagement, 15 x 110 mm [F] 12 x 148 mm [R], e-bike optimized
EKRAR	Giant TRA HD, Dynamic Balanced Lacing (D.B.L.)
DÄCK	Maxxis Assegai 29 X 2.50-inch Foldable, TLR, EXO+, 3C MaxxGrip [F], Maxxis Minion DHR II 27.5 x 2.4-inch Foldable, TLR, EXO+, MaxxTerra [R]
EXTRAFUNKTIONER	Giant Aegis Tire Checker, included tire pressure management system (TPMS) Tubeless kit (liquid, valves, levers, manual, tool)
TILLBEHÖR	
BELYSNING	Optional: Giant Recon series e-bike lights available and direct-connect compatible
GRÄNSER	
COMBINED MAXIMUM LOAD LIMIT	156kg

Price: 76 000,00 kr

GEOMETRY

RAM	S			M			L			XL		
	LOW HIGH			LOW HIGH			LOW HIGH			LOW HIGH		
Vinkel sadelrör	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°	76,6°	77,0°	77,4°
Topprörets längd (mm)	568	567	566	605	604	603	630	629	628	662	661	660
Styrhuvud Längd (mm)	110			120			130			140		
Vinkel styrhuvud	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°	64,1°	64,5°	64,9°
Hjulbas (mm)	1200	1199	1197	1239	1237	1236	1267	1265	1264	1300	1299	1298
Kedjestagslängd (mm)	443	443	443	443	443	443	443	443	443	443	443	443
Stack (mm)	634	631	629	643	640	638	652	649	647	661	659	658
Reach (mm)	422	425	428	457	460	463	477	480	484	504	510	513
Vevlängd (mm)	155			155			155			155		

All specifications listed are subject to change without notice.