

TRANCE ADVANCED PRO 29 0

GIANT



SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S, M, L, XL
ΧΡΩΜΑΤΑ	Pulp Gray / Terracotta / Black Chrome
ΣΚΕΛΕΤΟΣ	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
ΠΙΡΟΥΝΙ	Fox 34 Factory, 130mm, GRIP 2 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
ΑΝΑΡΤΗΣΗ	Fox Float X Factory, lockout, 185/50, custom tuned for Giant
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Contact SLR Trail Integrated, Advanced Composite, 5-position adjustable, 800mm (760mm minimum cut width), 7/8/9° Back Sweep adjust system, meets DH test standard, GPS mount included
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Contact SLR Trail Integrated, Advanced Composite, 5-position adjustable, 40/45/50mm Reach, +3°/0°/-3° Adjust System
ΛΑΙΜΟΣ Σ'ΕΛΛΑΣ	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
Σ'ΕΛΛΑ	Giant Romero SL
ΠΕΝΤΑΛ	N/A
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	SRAM XX1 Eagle AXS Rocker Paddle, 1x12
ΝΤΕΡΑΓΓΕΡ ΕΜΠΡΟΣΘΙΟ	N/A
ΝΤΕΡΑΓΓΕΡ ΟΠΙΣΘΙΟ	SRAM XX1 Eagle AXS
ΦΡΕΝΑ	Shimano XTR BR-MT9120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
ΜΑΝΕΤΤΕΣ ΦΡΕΝΩΝ	Shimano XTR BL-M9120
CASETTE Ή ΕΛΕΥΘΕΡΟ	SRAM XG 1295, 12-52
ΑΛΥΣΙΔΑ	SRAM X01 Eagle
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	SRAM XX1 Eagle DUB SL, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS

ΣΤΕΦΑΝΙΑ	Zipp 3ZERO MOTO 29 carbon
ΚΕΝΤΡΑ	Zipp 3ZERO MOTO 29 carbon
ΑΚΤΙΝΕΣ	Zipp 3ZERO MOTO 29 carbon
ΕΛΑΣΤΙΚΑ	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRAS	tubeless prepared, 2.6" max tire size, 34t max chainring size, MRP V3 Carbon chain guide

ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	420		430		465		496	
Seat Tube Angle	77,2° 78,0°		76,3° 77,0°		76,3° 77,0°		76,3° 77,0°	
Top Tube Length (mm)	561 559		599 597		626 624		663 661	
Head Tube Length (mm)	100		110		120		130	
Head Tube Angle	65,4° 66,2°		65,5° 66,2°		65,5° 66,2°		65,5° 66,2°	
Fork Rake (mm)	44		44		44		44	
Trail (mm)	126 120		126 120		126 120		126 120	
Wheelbase (mm)	1166 1165		1195 1194		1224 1223		1263 1262	
Chain Stay Length (mm)	439 437		439 437		439 437		439 437	
Bottom Bracket Drop (mm)	45 35		45 35		45 35		45 35	
Stack (mm)	610 604		619 613		628 622		637 631	
Reach (mm)	422 430		447 455		472 480		507 515	
Stand Over Height (mm)	729 737		723 732		746 755		751 760	
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	40		40		50		50	
Crank Length (mm)	165		170		170		170	
Wheel Size	29"		29"		29"		29"	

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση