

TRANCE ADVANCED PRO 29 0

GIANT



SPECIFIKACIJE

OKVIR	
VELIČINE	S, M, L, XL
BOJE	Pulp Gray / Terracotta / Black Chrome
OKVIR	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
VILICA	Fox 34 Factory, 130mm, GRIP 2 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Float X Factory, lockout, 185/50, custom tuned for Giant
KOMPONENTE	
VOLAN	Giant Contact SLR Trail Integrated, Advanced Composite, 5-position adjustable, 800mm (760mm minimum cut width), 7/8/9° Back Sweep adjust system, meets DH test standard, GPS mount included
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
LULA VOLANA	Giant Contact SLR Trail Integrated, Advanced Composite, 5-position adjustable, 40/45/50mm Reach, +3°/0°/-3° Adjust System
CIJEV SJEDALA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SJEDALO	Giant Romero SL
PEDALE	N/A
POGON	
RUČICE MJENJAČA	SRAM XX1 Eagle AXS Rocker Paddle, 1x12
PREDNJI MJENJAČ	N/A
STRAŽNJI MJENJAČ	SRAM XX1 Eagle AXS
KOČNICE	Shimano XTR BR-MT9120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
RUČICE KOČNICA	Shimano XTR BL-M9120
KAZETA	SRAM XG 1295, 12-52
LANAC	SRAM X01 Eagle
POGON	SRAM XX1 Eagle DUB SL, 30t S:165mm, M:170mm, L:170mm, XL:170mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Zipp 3ZERO MOTO 29 carbon
NABE	Zipp 3ZERO MOTO 29 carbon
ŽBICE	Zipp 3ZERO MOTO 29 carbon
GUME	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
DODACI	tubeless prepared, 2.6" max tire size, 34t max chainring size, MRP V3 Carbon chain guide

GEOMETRIJA

OKVIR	S	M	L	X
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Dužina cijevi sjedala (mm)	420	430	465	495
Kut cijevi sjedala	77,2°	78,0°	76,3°	77,0°
Dužina gornje cijevi (mm)	561 559	599 597	626 624	660 658
Dužina prednje cijevi (mm)	100	110	120	130
Kut vilice	65,4°	66,2°	65,5°	66,2°
Zakrivljenost vilice (offset) (mm)	44	44	44	44
Staza (mm)	126 120	126 120	126 120	126 120
Međuosovinski razmak kotača (mm)	1166 1165	1195 1194	1224 1223	1253 1252
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	439 437	439 437	439 437	439 437
Položaj osovine pogona (mm)	45 35	45 35	45 35	45 35
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	610 604	619 613	628 622	637 631
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	422 430	447 455	472 480	497 505
Prekoračna visina (mm)	729 737	723 732	746 755	771 780
Širina volana (mm)	780	780	780	780
Dužina lule volana (mm)	40	40	50	50
Dužina poluge pedale (mm)	165	170	170	170
Veličina kotača	29"	29"	29"	29"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.