

TRANCE ADVANCED PRO 29 0



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Pulp Gray / Terracotta / Black Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
FORK	Fox 34 Factory, 130mm, GRIP 2 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
SHOCK	Fox Float X Factory, lockout, 185/50, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR Trail Integrated, Advanced Composite, 5-position adjustable, 800mm (760mm minimum cut width), 7/8/9° Back Sweep adjust system, meets DH test standard, GPS mount included
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SLR Trail Integrated, Advanced Composite, 5-position adjustable, 40/45/50mm Reach, +3°/0°/-3° Adjust System
SEATPOST	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM XX1 Eagle AXS Rocker Paddle, 1x12
FRONT DERAILEUR	N/A
REAR DERAILEUR	SRAM XX1 Eagle AXS
BRAKES	Shimano XTR BR-MT9120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
BRAKE LEVERS	Shimano XTR BL-M9120
CASSETTE	SRAM XG 1295, 12-52
CHAIN	SRAM X01 Eagle
CRANKSET	SRAM XX1 Eagle DUB SL, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Zipp 3ZERO MOTO 29 carbon
HUBS	Zipp 3ZERO MOTO 29 carbon
SPOKES	Zipp 3ZERO MOTO 29 carbon
TIRES	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRAS	tubeless prepared, 2.6" max tire size, 34t max chainring size, MRP V3 Carbon chain guide

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	420	430	465	496
Seat Tube Angle	77,2° 78,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°
Top Tube Length (mm)	561 559	599 597	626 624	663 661
Head Tube Length (mm)	100	110	120	130
Head Tube Angle	65,4° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°
Fork Rake (mm)	44	44	44	44
Trail (mm)	126 120	126 120	126 120	126 120
Wheelbase (mm)	1166 1165	1195 1194	1224 1223	1263 1262
Chain Stay Length (mm)	439 437	439 437	439 437	439 437
Bottom Bracket Drop (mm)	45 35	45 35	45 35	45 35
Stack (mm)	610 604	619 613	628 622	637 631
Reach (mm)	422 430	447 455	472 480	507 515
Stand Over Height (mm)	729 737	723 732	746 755	751 760
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	29"	29"	29"	29"

All specifications listed are subject to change without notice.