



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Pulp Gray / Terracotta / Black Chrome
OKVIR	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
VILICE	Fox 34 Factory, 130mm, GRIP 2 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Float X Factory, lockout, 185/50, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SLR Trail Integrated, Advanced Composite, 5-position adjustable, 800mm (760mm minimum cut width), 7/8/9° Back Sweep adjust system, meets DH test standard, GPS mount included
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SLR Trail Integrated, Advanced Composite, 5-position adjustable, 40/45/50mm Reach, +3°/0°/-3° Adjust System
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SEDEŽ	Giant Romero SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM XX1 Eagle AXS Rocker Paddle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM XX1 Eagle AXS
ZAVORE	Shimano XTR BR-MT9120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
ZAVORNE ROČICE	Shimano XTR BL-M9120
VERIŽNIK	SRAM XG 1295, 12-52
VERIGA	SRAM X01 Eagle
GONILKE Z VERIŽNIKI	SRAM XX1 Eagle DUB SL, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Zipp 3ZERO MOTO 29 carbon
PESTA	Zipp 3ZERO MOTO 29 carbon
NAPERE	Zipp 3ZERO MOTO 29 carbon
PLAŠČI	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
DODATKI	tubeless prepared, 2.6" max tire size, 34t max chainring size, MRP V3 Carbon chain guide

GEOMETRIJA

OKVIR	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Dolžina sedežne cevi (mm)	420	430	465	496
Kot sedežne cevi	77,2° 78,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°
Top Tube Length (mm)	561 559	599 597	626 624	663 661
Višina glave okvirja (mm)	100	110	120	130
Krmilni kot	65,4° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	126 120	126 120	126 120	126 120
Medosna razdalja (mm)	1166 1165	1195 1194	1224 1223	1263 1262
Dolžina cevi ob verigi (mm)	439 437	439 437	439 437	439 437
Bottom Bracket Drop (mm)	45 35	45 35	45 35	45 35
Oddaljenost zgornje cevi od gonilne osi (mm)	610 604	619 613	628 622	637 631
Doseg (mm)	422 430	447 455	472 480	507 515
Višina zgornje cevi (mm)	729 737	723 732	746 755	751 760
Širina krmila (mm)	780	780	780	780
Dolžina opore krmila (mm)	40	40	50	50
Dolžina gonilke (mm)	165	170	170	170
Velikost obročnikov	29"	29"	29"	29"

Vse navedene specifikacije se lahko spremenijo brez obvestila.