

TRANCE ADVANCED PRO 29 1



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Carbon / Black Diamond / Chrome
RUNKO	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
HAARUKKA	Fox 34 Performance Elite Live Valve, 130mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
ISKUNVAIMENNIN	Fox Performance Elite Live Valve, 185/50, custom tuned for Giant
KOMPONENTIT	
OHJAUSTANKO	Giant Contact SLR TR35, composite, 780x35mm
GRIPIT	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OHJAINKANNATIN	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SATULATOLPPA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SATULA	Giant Romero SL
POLKIMET	N/A
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Deore XT SL-M8100, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	Shimano Deore XT RD-M8100
JARRUT	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
JARRUKAHVAT	Shimano Deore XT BL-M8100
RATASPAKKA	Shimano Deore XT M8100, 10x51
KETJUT	KMC X-12
KAMPISARJA	Praxis Girder Carbon, 30t S:165mm, M:170mm, L:170mm, XL:170mm
KESKIÖ	Shimano, press fit

RENKAAT	
VANTEET	Giant TRX 2 Carbon 29 WheelSystem
NAVAT	Giant TRX 2 Carbon 29 WheelSystem
PINNAT	Giant TRX 2 Carbon 29 WheelSystem
RENKAAT	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
LISÄTIEDOT	tubeless prepared, 2.6" max tire size, 34t max chainring size

Suositusinta: 7 049,00 €

GEOMETRIA

RUNKO	S	M	L
	LOW HIGH	LOW HIGH	LOW HIGH
Satulaputken pituus (mm)	420	430	465
Satulaputken kulma	77,2° 78,0°	76,3° 77,0°	76,3° 77,0°
Vaakaputken pituus (mm)	561 559	599 597	626 624
Emäputken pituus (mm)	100	110	120
Emäputken kulma	65,4° 66,2°	65,5° 66,2°	65,5° 66,2°
Haarukan offset (mm)	44	44	44
Trail-mitta (mm)	126 120	126 120	126 120
Akseliväli (mm)	1166 1165	1195 1194	1224 1223
Takahaarukan alaputken pituus (mm)	439 437	439 437	439 437
Keskiön pudotus (mm)	45 35	45 35	45 35
Stack-mitta (mm)	610 604	619 613	628 622
Reach-mitta (mm)	422 430	447 455	472 480
Standover-mitta (mm)	729 737	723 732	746 755
Ohjaustangon leveys (mm)	780	780	780
Ohjainkannattimen pituus (mm)	40	40	50
Kammen pituus (mm)	165	170	170
Rengaskoko	29"	29"	29"

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.