TRANCE ADVANCED PRO 29 1

SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Gloss Cordovan/Matte Cordovan/Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle, integrated downtube storage
VOORVORK	Fox 34 Factory Live Valve, 130mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
DEMPER	Fox Factory Live Valve, 185/50, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact SLR TR35, composite, 780x35mm
HANDVATTEN	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STUURPEN	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
ZADELPEN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm
ZADEL	Giant Romero SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM GX Eagle, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM GX Eagle
REMMEN	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
REMHENDELS	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX, 10x52
AANDRIJVING	SRAM GX
CRANKSET	SRAM GX, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NAVEN	Front : Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPAKEN	Sapim
BANDEN	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRA'S	tubeless prepared, 2.6" max tire size, 34t max chainring size

Adviesprijs: € 7.699,00

GEOMETRIE

FRAME	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Zitbuis Lengte (mm)	420	430	465	496
Zitbuis Hoek	77,2° | 78,0°	76,3° | 77,0°	76,3° | 77,0°	76,3° | 77,0°
Frame Lengte (horizontaal) (mm)	561 | 559	599 | 597	626 | 624	663 | 661
Balhoofdbuis Lengte (mm)	100	110	120	130
Balhoofdbuis Hoek	65,4° | 66,2°	65,5° | 66,2°	65,5° | 66,2°	65,5° | 66,2°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	126 | 120	126 | 120	126 | 120	126 | 120
Wielbasis (mm)	1166 | 1165	1195 | 1194	1124 | 1123	1263 | 1262
Liggende achtervork lengte (mm)	439 | 437	439 | 437	439 | 437	439 | 437
Bottom Bracket Drop (mm)	45 | 35	45 | 35	45 | 35	45 | 35
Stack (mm)	610 | 604	619 | 613	628 | 622	637 | 631
Reach (mm)	422 | 431	447 | 456	472 | 480	507 | 515
Stand Over Height (mm)	729 | 737	723 | 732	746 | 755	751 | 760
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	40	40	50	50
Cranklengte (mm)	165	170	170	170
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.