



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Carbon / Black Diamond / Chrome
OKVIR	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
VILICE	Fox 34 Performance Elite Live Valve, 130mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Performance Elite Live Valve, 185/50, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SLR TR35, composite, 780x35mm
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SEDEŽ	Giant Romero SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano Deore XT SL-M8100, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore XT RD-M8100
ZAVORE	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
ZAVORNE ROČICE	Shimano Deore XT BL-M8100
VERIŽNIK	Shimano Deore XT M8100, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Praxis Girder Carbon, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant TRX 2 Carbon 29 WheelSystem
PESTA	Giant TRX 2 Carbon 29 WheelSystem
NAPERE	Giant TRX 2 Carbon 29 WheelSystem
PLAŠČI	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
DODATKI	tubeless prepared, 2.6" max tire size, 34t max chainring size

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	420		430		465		496	
Kot sedežne cevi	77,2° 78,0°		76,3° 77,0°		76,3° 77,0°		76,3° 77,0°	
Top Tube Length (mm)	561 559		599 597		626 624		663 661	
Višina glave okvirja (mm)	100		110		120		130	
Krmilni kot	65,4° 66,2°		65,5° 66,2°		65,5° 66,2°		65,5° 66,2°	
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	126 120		126 120		126 120		126 120	
Medosna razdalja (mm)	1166 1165		1195 1194		1224 1223		1263 1262	
Dolžina cevi ob verigi (mm)	439 437		439 437		439 437		439 437	
Bottom Bracket Drop (mm)	45 35		45 35		45 35		45 35	
Oddaljenost zgornje cevi od gonilne osi (mm)	610 604		619 613		628 622		637 631	
Doseg (mm)	422 430		447 455		472 480		507 515	
Višina zgornje cevi (mm)	729 737		723 732		746 755		751 760	
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	40		40		50		50	
Dolžina gonilke (mm)	165		170		170		170	
Velikost obročnikov	29"		29"		29"		29"	

Vse navedene specifikacije se lahko spremenijo brez obvestila.