



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Gloss Cordovan/Matte Cordovan/Chrome
OKVIR	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle, integrated downtube storage
VILICE	Fox 34 Factory Live Valve, 130mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
AMORTIZER	Fox Factory Live Valve, 185/50, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SLR TR35, composite, 780x35mm
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm
SEDEŽ	Giant Romero SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM GX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle
ZAVORE	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-66 rotors [F]180mm, [R]180mm
ZAVORNE ROČICE	Shimano Deore XT BL-M8100
VERIŽNIK	SRAM GX, 10x52
VERIGA	SRAM GX
GONILKE Z VERIŽNIKI	SRAM GX, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
PESTA	Front : Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
NAPERE	Sapim
PLAŠČI	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
DODATKI	tubeless prepared, 2.6" max tire size, 34t max chainring size

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	420	430	465	496				
Kot sedežne cevi	77,2°	78,0°	76,3°	77,0°	76,3°	77,0°	76,3°	77,0°
Top Tube Length (mm)	561	559	599	597	626	624	663	661
Višina glave okvirja (mm)	100	110	120	130				
Krmilni kot	65,4°	66,2°	65,5°	66,2°	65,5°	66,2°	65,5°	66,2°
Zamik vpetja osi (mm)	44	44	44	44				
Trail (mm)	126	120	126	120	126	120	126	120
Medosna razdalja (mm)	1166	1165	1195	1194	1124	1123	1263	1262
Dolžina cevi ob verigi (mm)	439	437	439	437	439	437	439	437
Bottom Bracket Drop (mm)	45	35	45	35	45	35	45	35
Oddaljenost zgornje cevi od gonilne osi (mm)	610	604	619	613	628	622	637	631
Doseg (mm)	422	431	447	456	472	480	507	515
Višina zgornje cevi (mm)	729	737	723	732	746	755	751	760
Širina krmila (mm)	780	780	780	780				
Dolžina opore krmila (mm)	40	40	50	50				
Dolžina gonilke (mm)	165	170	170	170				
Velikost obročnikov	29"	29"	29"	29"				

Vse navedene specifikacije se lahko spremenijo brez obvestila.