

TRANCE ADVANCED PRO 29 2

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Metal/Black / Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle
VOORVORK	Fox 34 Float Rhythm, 130mm, GRIP damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
DEMPER	Fox Float DPS Performance, 185/50, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact TR35, 780x35mm
HANDVATTEN	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STUURPEN	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
ZADELPEN	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
ZADEL	Giant Romero SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano SLX SL-M7100, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano SLX RD-M7100
REMMEN	Shimano Deore XT BR-M6120, hydraulic, Shimano RT-56 rotors [F]180mm, [R]180mm
REMHENDELS	Shimano Deore BL-M6100
CASSETTE	Shimano SLX, 10x51
AANDRIJVING	KMC X-12
CRANKSET	Shimano MT512-1, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

WIELSET	
VELGEN	Giant TRX 2 Carbon 29 WheelSystem
NAVEN	Giant TRX 2 Carbon 29 WheelSystem
SPAKEN	Giant TRX 2 Carbon 29 WheelSystem
BANDEN	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Aggressor 29x2.5, EXO, TR, tubeless
EXTRA'S	tubeless prepared, 2.6" max tire size, 34t max chainring size

Adviesprijs: € 4.999,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	420		430		465		496	
Zitbuis Hoek	77,2°	78,0°	76,3°	77,0°	76,3°	77,0°	76,3°	77,0°
Frame Lengte (horizontaal) (mm)	561	559	599	597	626	624	663	661
Balhoofdbuis Lengte (mm)	100		110		120		130	
Balhoofdbuis Hoek	65,4°	66,2°	65,5°	66,2°	65,5°	66,2°	65,5°	66,2°
Vork Sprong (mm)	44		44		44		44	
Naloop (mm)	126	120	126	120	126	120	126	120
Wielbasis (mm)	1166	1165	1195	1194	1224	1223	1263	1262
Liggende achtervork lengte (mm)	439	437	439	437	439	437	439	437
Bottom Bracket Drop (mm)	45	35	45	35	45	35	45	35
Stack (mm)	610	604	619	613	628	622	637	631
Reach (mm)	422	430	447	455	472	480	507	515
Stand Over Height (mm)	729	737	723	732	746	755	751	760
Stuurpen breedte (mm)	780		780		780		780	
Stuurpen Lengte (mm)	40		40		50		50	
Cranklengte (mm)	165		170		170		170	
Wielmaat	29"		29"		29"		29"	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.