

TRANCE ADVANCED PRO 29 FRAME

GIANT



SPECIFIKACIJE

| OKVIR     |                                                                                                            |
|-----------|------------------------------------------------------------------------------------------------------------|
| VELIKOSTI | S, M, L, XL                                                                                                |
| BARVE     | Bronze Slate                                                                                               |
| OKVIR     | Advanced-Grade Composite front and rear triangles, 120mm Maestro suspension, flip chip, 12x148mm thru-axle |
| AMORTIZER | Fox Float X Factory, lockout, 185/50, custom tuned for Giant                                               |

GEOMETRIJA

| OKVIR                                        | S             | M             | L             | XL            |
|----------------------------------------------|---------------|---------------|---------------|---------------|
|                                              | LOW   HIGH    | LOW   HIGH    | LOW   HIGH    | LOW   HIGH    |
| Dolžina sedežne cevi (mm)                    | 420           | 430           | 465           | 496           |
| Kot sedežne cevi                             | 77,2°   78,0° | 76,3°   77,0° | 76,3°   77,0° | 76,3°   77,0° |
| Top Tube Length (mm)                         | 561   559     | 599   597     | 626   624     | 663   661     |
| Višina glave okvirja (mm)                    | 100           | 110           | 120           | 130           |
| Krmilni kot                                  | 65,4°   66,2° | 65,5°   66,2° | 65,5°   66,2° | 65,5°   66,2° |
| Zamik vpetja osi (mm)                        | 44            | 44            | 44            | 44            |
| Trail (mm)                                   | 126   120     | 126   120     | 126   120     | 126   120     |
| Medosna razdalja (mm)                        | 1166   1165   | 1195   1194   | 1224   1223   | 1263   1262   |
| Dolžina cevi ob verigi (mm)                  | 439   437     | 439   437     | 439   437     | 439   437     |
| Bottom Bracket Drop (mm)                     | 45   35       | 45   35       | 45   35       | 45   35       |
| Oddaljenost zgornje cevi od gonilne osi (mm) | 610   604     | 619   613     | 628   622     | 637   631     |
| Doseg (mm)                                   | 422   430     | 447   455     | 472   480     | 507   515     |
| Višina zgornje cevi (mm)                     | 729   737     | 723   732     | 746   755     | 751   760     |
| Širina krmila (mm)                           | 780           | 780           | 780           | 780           |
| Dolžina opore krmila (mm)                    | 40            | 40            | 50            | 50            |
| Dolžina gonilke (mm)                         | 165           | 170           | 170           | 170           |
| Velikost obročnikov                          | 29"           | 29"           | 29"           | 29"           |

Vse navedene specifikacije se lahko spremenijo brez obvestila.