

TRANCE X 1

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Smoke Metal/Chrome, Dried Chili
RAMME	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORGAFFEL	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
BAGDÆMPER	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMPONENTER	
STYR	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GREB / STYRBÅND	Giant Tactal Pro Single Lock-On, 132x35mm
FREMPIND	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SADELPIND	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADEL	Giant Romero SL
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	Shimano SLX M-7100, I-Spec EV, 1x12
FORSKIFTER	N/A
BAGSKIFTER	Shimano SLX M-7100, Shadow +
BREMSE	Shimano BR-MT520, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BREMSEGREB	Shimano Deore BL-MT501
KASSETTE	Shimano SLX M7100, 10x51
KÆDE	KMC X-12
KRANKSÆT	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
KRANKBOKS	Shimano Press Fit

HJUL	
FÆLGE	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAV	[F] Giant Alloy, 6 Bolt [R] TRA HE, Alloy, 72 Pawl Driver, 6 bolt
EGER	Sapim, 28, straight pull, DBL Technology
DÆK	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EKSTRA	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Pris: 36.999,00 kr.

GEOMETRI

RAMME	S			M			L			XL	
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID
Sadelrørlængde (mm)	400			425			450			475	
Sadelpindindsætningsdybde (mm)	280			305			330			355	
Sadelrørvinkel	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°
Overrørsrørlængde (mm)	571	570	569	602	601	600	624	623	622	657	656
Kronrørlængde (mm)	100			105			115			125	
Kronrørvinkel	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°
Forgaffel fremspring (rake) (mm)	44			44			44			44	
Sti (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	133,9	131,3
Akselafstand (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280
Kædestagslængde (mm)	440	439	438	440	439	438	440	439	438	440	439
Krankboks drop (mm)	40	35	30	40	35	30	40	35	30	40	35
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510
Skridthøjde (mm)	732	737	742	746	750	755	763	768	773	781	758
Styrbredde (mm)	800			800			800			800	
Fremspindslængde (mm)	40			40			50			50	
Pedalarmslængde (mm)	165			170			170			170	
Hjulstørrelse	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]	

Alle de anførte specifikationer kan ændres uden varsel.