

TRANCE X 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Smoke Metal/Chrome
FRAME	ALUXX SL-grade aluminium front and rear triangles, 140mm Maestro suspension, flip chip - Maestro 3, flip chip - headset, 12x148mm thru-axle
FORK	Fox 36 Float Performance, GRIP damper, 44mm offset, 150mm, 15x110 Kabolt, custom tuned for Giant
SHOCK	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch Adjustable, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	Shimano SLX SL-M7100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX RD-M7100
BRAKES	Shimano Deore BR-MT520, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore BL-MT501
CASSETTE	Shimano SLX, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano M512, 30t, 55mm chainline
BOTTOM BRACKET	Shimano Press Fit

WHEELS	
RIMS	Giant TRA, 29" hookless aluXX wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 SP spokes, DBL technology, MS driver body
HUBS	[F] Giant Alloy, 6 Bolt [R] TRA HE, Alloy, 72 Pawl Driver, 6 bolt
SPOKES	Sapim, 28, straight pull, DBL Technology
TYRES	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAS	Factory tubeless set up
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	34t

Price: £3,999.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3	128.5
Wheelbase (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	1279
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Stand Over Height (mm)	732	737	742	746	750	755	763	768	773	781	785	790
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.