

# TRANCE X 1

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLOURS</b>	Smoke Metal/Chrome
<b>FRAME</b>	ALUXX SL-grade aluminium front and rear triangles, 140mm Maestro suspension, flip chip - Maestro 3, flip chip - headset, 12x148mm thru-axle
<b>FORK</b>	Fox 36 Float Performance, GRIP damper, 44mm offset, 150mm, 15x110 Kabolt, custom tuned for Giant
<b>SHOCK</b>	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, 780x35mm, 20mm rise
<b>GRIPS</b>	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
<b>STEM</b>	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
<b>SEATPOST</b>	Giant Contact Switch Adjustable, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
<b>SADDLE</b>	Giant Romero
<b>PEDALS</b>	PEDALS NOT SUPPLIED
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano SLX SL-M7100, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano SLX RD-M7100
<b>BRAKES</b>	Shimano Deore BR-MT520, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
<b>BRAKE LEVERS</b>	Shimano Deore BL-MT501
<b>CASSETTE</b>	Shimano SLX, 10x51
<b>CHAIN</b>	KMC X-12
<b>CRANKSET</b>	Shimano M512, 30t, 55mm chainline
<b>BOTTOM BRACKET</b>	Shimano Press Fit

WHEELS	
<b>RIMS</b>	Giant TRA, 29" hookless aluux wheelsystem, 30mm IW, 40mm OW, 21mm H,72t POE, 28 SP spokes, DBL technology, MS driver body
<b>HUBS</b>	[F] Giant Alloy, 6 Bolt [R] TRA HE, Alloy, 72 Pawl Driver, 6 bolt
<b>SPOKES</b>	Sapim, 28, straight pull, DBL Technology
<b>TYRES</b>	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
<b>EXTRAS</b>	Factory tubeless set up, 2.5" max tyre size, 34t max chainring size

**Price: €4,599.00**

## GEOMETRY

FRAME	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450		
Seat Post Insertion Depth (mm)	280			305			330		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622
Head Tube Length (mm)	100			105			115		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°
Fork Rake (mm)	44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5
Wheelbase (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625
Reach (mm)	426	430	434	456	460	464	476	480	484
Stand Over Height (mm)	732	737	742	746	750	755	763	768	773
Handlebar Width (mm)	800			800			800		
Stem Length (mm)	40			40			50		
Crank Length (mm)	165			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All specifications listed are subject to change without notice.