

TRANCE X 1



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Smoke Metal/Chrome, Dried Chili
RUNKO	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
HAARUKKA	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
ISKUNVAIMENNIN	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMPONENTIT	
OHJAUSTANKO	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPIT	Giant Tactal Pro Single Lock-On, 132x35mm
OHJAINKANNATIN	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SATULATOLPPA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SATULA	Giant Romero SL
POLKIMET	N/A
VOIMANSIIRTO	
VAIHDEVIPU	Shimano SLX M-7100, I-Spec EV, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	Shimano SLX M-7100, Shadow +
JARRUT	Shimano BR-MT520, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
JARRUKAHVAT	Shimano Deore BL-MT501
RATASPAKKA	Shimano SLX M7100, 10x51
KETJUT	KMC X-12
KAMPISARJA	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
KESKIÖ	Shimano Press Fit

RENKAAT	
VANTEET	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAVAT	[F] Giant Alloy, 6 Bolt [R] TRA HE, Alloy, 72 Pawl Driver, 6 bolt
PINNAT	Sapim, 28, straight pull, DBL Technology
RENKAAT	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
LISÄTIEDOT	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Suositusinta: 4 979,00 €

GEOMETRIA

RUNKO	M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Satulaputken pituus (mm)	425			450			475		
Satulatolpan asennussyvyys (mm)	305			330			355		
Satulaputken kulma	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Vaakaputken pituus (mm)	602	601	600	624	623	622	657	656	655
Emäputken pituus (mm)	105			115			125		
Emäputken kulma	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Haarukan offset (mm)	44			44			44		
Trail-mitta (mm)	134	131,3	128,5	133,9	131,3	128,5	133,9	131,3	128,6
Akseliväli (mm)	1222	1222	1221	1246	1246	1245	1281	1280	1280
Takahaarukan alaputken pituus (mm)	440	439	438	440	439	438	440	439	438
Keskiön pudotus (mm)	40	35	30	40	35	30	40	35	30
Stack-mitta (mm)	621	619	616	631	628	625	640	637	634
Reach-mitta (mm)	456	460	464	476	480	484	507	510	514
Standover-mitta (mm)	746	750	755	763	768	773	781	785	790
Ohjaustangon leveys (mm)	800			800			800		
Ohjainkannattimen pituus (mm)	40			50			50		
Kammen pituus (mm)	170			170			170		
Rengaskoko	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Kaikki ilmoitettut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.