

TRANCE X 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Smoke Metal/Chrome
FRAME	ALUXX SL-grade aluminum front and rear triangles, 140mm Maestro suspension, flip chip - Maestro 3, flip chip - headset, 12x148mm thru-axle, integrated downtube storage
FORK	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 20mm rise, alloy, 780x35mm
GRIPS	Giant Tactal Pro single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch Adjustable, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L/XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano SLX M-7100, I-Spec EV, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano SLX M-7100, Shadow +
BRAKES	Shimano BR-MT520, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore BL-MT501
CASSETTE	Shimano SLX M7100, 10x51
CHAIN	KMC X-12
CRANKSET	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano Press Fit

WHEELS	
RIMS	Giant TRA WheelSystem, 6069 alloy, welded, 30mm IW, 40mm OW, 21mm H, Wide Guard technology, [F] 29, [R] 29
HUBS	[F] Giant MTB alloy, 6-bolt, sealed [R] Giant MTB alloy, 6 bolt, 72t POE, 6-pawl, sealed
SPOKES	Sapim Laser straight pull, DBL technology
TIRES	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, integrated down tube storage bag

Suggested Retail Price (CDN): \$4,499.00

FRAME GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8° 77.2° 77.5°			76.8° 77.2° 77.5°			76.8° 77.2° 77.5°			76.8° 77.2° 77.5°		
Top Tube Length (mm)	571 570 569			602 601 600			624 623 622			657 656 655		
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 65.1°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1 131.3 128.4	134		131.3 128.5	133.9		131.3 128.5	133.9		131.3 128.5	133.9	
Wheelbase (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245			1281 1280 1279		
Chain Stay Length (mm)	440 439 438			440 439 438			440 439 438			440 439 438		
Bottom Bracket Drop (mm)	40 35 30			40 35 30			40 35 30			40 35 30		
Stack (mm)	617 614 611			621 619 616			631 628 625			640 637 634		
Reach (mm)	426 430 434			456 460 464			476 480 484			507 510 514		
Stand Over Height (mm)	732 737 742			746 750 755			763 768 773			781 785 789		
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All prices and specifications are subject to change without notice.