

TRANCE X 1



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Smoke Metal/Chrome, Dried Chili
TELAIO	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORCELLA	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMMORTIZZATORE	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTISTICA	
MANUBRIO	Giant Contact TR35, alloy, 780x35mm, 20mm rise
MANOPOLE	Giant Tactal Pro Single Lock-On, 132x35mm
ATTACCO MANUBRIO	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
REGGISELLA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLA	Giant Romero SL
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano SLX M-7100, I-Spec EV, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	Shimano SLX M-7100, Shadow +
FRENI	Shimano BR-MT520, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
COMANDI FRENO	Shimano Deore BL-MT501
PACCO PIGNONI	Shimano SLX M7100, 10x51
CATENA	KMC X-12
GUARNITURA	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRALE	Shimano Press Fit

RUOTE	
CERCHI	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
MOZZI	[F] Giant Alloy, 6 Bolt [R] TRA HE, Alloy, 72 Pawl Driver, 6 bolt
RAGGI	Sapim, 28, straight pull, DBL Technology
COPERTONI	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRA	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Prezzo: € 4.699

GEOMETRIA

TELAIO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Lunghezza Tubo Sella (mm)	400			425			450			475
Profondità inserimento reggisella (mm)	280			305			330			355
Angolo Tubo Sella	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°
Lunghezza Tubo Orizzontale (mm)	571	570	569	602	601	600	624	623	622	657
Lunghezza Tubo Sterzo (mm)	100			105			115			125
Angolo Sterzo	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°
Rake Forcella (mm)	44			44			44			44
Avancorsa (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	133,9
Interasse (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281
Lunghezza Carro Posteriore (mm)	440	439	438	440	439	438	440	439	438	440
Drop Movimento Centrale (mm)	40	35	30	40	35	30	40	35	30	40
Stack (mm)	617	614	611	621	619	616	631	628	625	640
Reach (mm)	426	430	434	456	460	464	476	480	484	507
Altezza stand over (mm)	732	737	742	746	750	755	763	768	773	781
Larghezza Manubrio c/c (mm)	800			800			800			800
Lunghezza Attacco Manubrio (mm)	40			40			50			50
Lunghezza Pedivella (mm)	165			170			170			170
Dimensione Ruote	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.