

TRANCE X 1



스펙

프레임	
사이즈	S, M, L, XL
색상	Smoke Metal/Chrome, Dried Chili
프레임	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
포크	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
서스펜션	Fox Float Performance, 185/52.5, custom tuned for Giant
부품	
핸들바	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
스템	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
시프트스트	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
안장	Giant Romero SL
페달	N/A
구동계	
변속기	Shimano SLX M-7100, I-Spec EV, 1x12
앞 변속기	N/A
뒷 변속기	Shimano SLX M-7100, Shadow +
브레이크	Shimano BR-MT520, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
브레이크 레버	Shimano Deore BL-MT501
스프라켓	Shimano SLX M7100, 10x51
체인	KMC X-12
크랭크 셋	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BB	Shimano Press Fit

바퀴	
립	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
허브	[F] Giant Alloy, 6 Bolt [R] TRA HE, Alloy, 72 Pawl Driver, 6 bolt
스포크	Sapim, 28, straight pull, DBL Technology
타이어	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
추가 기능	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

가격: ₩4,590,000

지오메트리

프레임	S	M
	LOW MID HIGH	LOW MID HIGH
시트 튜브 길이 (mm)	400	425
Seat Post Insertion Depth (mm)	280	305
시트 튜브 각도	76.8° 77.2° 77.5°	76.8° 77.2° 77.5°
타입튜브 길이 (mm)	571 570 569	602 601 600
헤드 튜브 길이 (mm)	100	105
헤드튜브 각도	64.4° 64.8° 65.1°	64.4° 64.8° 65.1°
포크 레이크 (mm)	44	44
트레일 (mm)	134.1 131.3 128.4	134 131.3 128.5
휠베이스 (mm)	1190 1190 1189	1222 1222 1221
체인스테이 길이 (mm)	440 439 438	440 439 438
BB (mm)	40 35 30	40 35 30
스택 (mm)	617 614 611	621 619 616
범위 (mm)	426 430 434	456 460 464
스탠드 오버 (mm)	732 737 742	746 750 755
핸들바 폭 (mm)	800	800
스템 길이 (mm)	40	40
크랭크 길이 (mm)	165	170
휠사이즈	[F] 29" [R]	[F] 29" [R]

상기 스펙은 글로벌 스펙이며, 실제 구성과 차이가 있을 수 있습니다. 정확한 스펙은 매장을 방문하여 확인해주시기 바랍니다.