

TRANCE X 1

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Smoke Metal/Chrome
FRAME	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VOORVORK	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
DEMPER	Fox Float Performance, 185/52.5, custom tuned for Giant
ONDERDELEN	
STUUR	Giant Contact TR35, alloy, 780x35mm, 20mm rise
HANDVATTEN	Giant Tactal Pro Single Lock-On, 132x35mm
STUURPEN	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
ZADELPEN	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
ZADEL	Giant Romero SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	Shimano SLX M-7100, I-Spec EV, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	Shimano SLX M-7100, Shadow +
REMMEN	Shimano BR-MT520, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
REMHENDELS	Shimano Deore BL-MT501
CASSETTE	Shimano SLX M7100, 10x51
AANDRIJVING	KMC X-12
CRANKSET	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano Press Fit

WIELSET	
VELGEN	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAVEN	[F] Giant Alloy, 6 Bolt [R] TRA HE, Alloy, 72 Pawl Driver, 6 bolt
SPAKEN	Sapim, 28, straight pull, DBL Technology
BANDEN	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRA'S	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Adviesprijs: € 4.799,00

GEOMETRIE

FRAME	S			M			L			XL	
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID
Zitbuis Lengte (mm)	400	425	450	475							
Seat Post Insertion Depth (mm)	280	305	330	355							
Zitbuis Hoek	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°
Frame Lengte (horizontaal) (mm)	571 570 569	602 601 600	624 623 622	657 656 655							
Balhoofdbuis Lengte (mm)	100	105	115	125							
Balhoofdbuis Hoek	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°
Vork Srong (mm)	44	44	44	44							
Naloop (mm)	134,1 131,3 128,4	134 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5
Wielbasis (mm)	1190 1190 1189	1222 1222 1221	1246 1246 1245	1281 1280							
Liggende achtervork lengte (mm)	440 439 438	440 439 438	440 439 438	440 439 438	440 439 438	440 439 438	440 439 438	440 439 438	440 439 438	440 439 438	440 439 438
Bottom Bracket Drop (mm)	40 35 30	40 35 30	40 35 30	40 35 30							
Stack (mm)	617 614 611	621 619 616	631 628 625	640 637 634							
Reach (mm)	426 430 434	456 460 464	476 480 484	507 510 514							
Stand Over Height (mm)	732 737 742	746 750 755	763 768 773	781 758 735							
Stuur breedte (mm)	800	800	800	800							
Stuurpen Lengte (mm)	40	40	50	50							
Cranklengte (mm)	165	170	170	170							
Wielmaat	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]							

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.