

TRANCE X 1



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	S, M, L, XL
FARBY	Black
RÁM	ALUXX SL-grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VIDLICA	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
TLMIČ	Fox Float Performance, 185/52.5
KOMPONENTY	
RIADIDLÁ	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPY	Giant Tactal Pro Single Lock-On, 132x35mm
PREDSTAVEC	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEDOVKA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDADLO	Giant Romero SL
PEDÁLE	N/A
POHON	
RADENIE	SRAM Eagle 90, 1x12
PREŠMYKAČ	N/A
PREHADZOVAČKA	SRAM Eagle 90 Transmission
BRZDY	TRP EVO Expert HD-M8040, hydraulic, TRP-SO6E, 6-bolt rotors [F]180mm, [R]180mm
BRZDOVÉ PÁKY	TRP EVO Expert
KAZETA	SRAM XS 1270, 10x52
REŤAZ	SRAM 70 Transmission
KLUKY	SRAM Eagle 90 T-Type, 30t XS: 165mm, S:165mm, M:165mm, L:165mm, XL:165mm
STREDOVÉ ZLOŽENIE	SRAM DUB, Press Fit

KOLESÁ	
RÁFIKY	Giant TRA WheelSystem, 6069 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NÁBOJE	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, MicroSpline driver body
ŠPICE	Sapim, 28, straight pull, DBL Technology
PNEUMATIKY	[F] Maxxis Assegai, 29x2.5 WT, 60 tpi, MaxxTerra, EXO, TR [R] Maxxis DHR II 29x2.4 WT, 60 tpi, MaxxTerra, TR, tubeless
DOPLNKY	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Cena: 4 699 €

GEOMETRIA

RÁM	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dĺžka sedlovej trubky (mm)	400			425			450		
Hĺbka vloženia sedlovky (mm)	280			305			330		
Uhol sedlovej trubky	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Dĺžka hornej rámovej trubky (mm)	571	570	569	602	601	600	624	623	622
Dĺžka hlavovej trubky (mm)	100			105			115		
Uhol hlavovej trubky	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Offset vidlice (mm)	44			44			44		
Trail (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,4
Rázvor (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245
Dĺžka zadnej stavby (mm)	440	439	438	440	439	438	440	439	438
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	40	35	30	40	35	30	40	35	30
Stack - výška riadenia (mm)	617	614	611	621	619	616	631	628	625
Reach (mm)	426	430	434	456	460	464	476	480	484
Výška rámu od zeme (mm)	732	737	742	746	750	755	763	768	773
Šírka riaditok (mm)	800			800			800		
Dĺžka predstavca (mm)	40			40			50		
Dĺžka klúk (mm)	165			170			170		

Všetky ceny a špecifikácie sa môžu zmeniť bez predchádzajúceho upozornenia.