



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Black / Smoke Metal / Chrome
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 145mm Maestro suspension, flip chip, 12x148mm thru-axle
VILICE	Fox 36 Performance Elite, GRIP 2 damper, 37mm offset, 160mm, 15x110 Kabolt X, custom tuned for Giant
AMORTIZER	Fox Float X Performance Elite, lockout, 185/55, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SEDEŽ	Giant Romero
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM GX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle
ZAVORE	SRAM Code R, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
ZAVORNE ROČICE	SRAM Code
VERIŽNIK	SRAM XG-1275, 10x52
VERIGA	SRAM GX Eagle
GONILKE Z VERIŽNIKI	SRAM GX Eagle, 32t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant TR-1 27.5 WheelSystem
PESTA	Giant TR-1 27.5 WheelSystem
NAPERE	Giant TR-1 27.5 WheelSystem
PLAŠČI	[F] Maxxis Assegai 27.5x2.6, 3C MaxxTerra, EXO, TR [R] Maxxis Minion DHRII 27.5x2.6, 3C MaxxTerra, EXO, TR, tubeless
DODATKI	tubeless prepared, 2.6" max tire size, 34t max chainring size, MRP AMG CS chain guide

GEOMETRIJA

OKVIR	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Dolžina sedežne cevi (mm)	420	430	465	496
Kot sedežne cevi	77,2° 78,0°	76,3° 77,0°	76,3° 77,0°	76,3° 77,0°
Top Tube Length (mm)	562 560	595 593	622 620	649 647
Višina glave okvirja (mm)	95	105	115	125
Krmilni kot	63,7° 64,5°	63,8° 64,5°	63,8° 64,5°	63,8° 64,5°
Zamik vpetja osi (mm)	37	37	37	37
Trail (mm)	138 132	138 132	138 132	138 132
Medosna razdalja (mm)	1179 1177	1203 1202	1233 1231	1262 1260
Dolžina cevi ob verigi (mm)	433 430	433 430	433 430	433 430
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Oddaljenost zgornje cevi od gonilne osi (mm)	596 590	605 599	614 608	623 617
Doseg (mm)	427 435	447 455	472 480	497 505
Višina zgornje cevi (mm)	709 718	714 723	740 750	762 772
Širina krmila (mm)	800	800	800	800
Dolžina opore krmila (mm)	40	40	50	50
Dolžina gonilke (mm)	165	170	170	170
Velikost obročnikov	27,5"	27,5"	27,5"	27,5"

Vse navedene specifikacije se lahko spremenijo brez obvestila.