

TRANCE X 1



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Smoke Metal/Chrome, Dried Chili
RAM	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
GAFFEL	Fox 36 Float Performance, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
BAKDÄMPARE	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMPONENTER	
STYRE	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GREPPAR	Giant Tactal Pro Single Lock-On, 132x35mm
STAM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SADELSTOLPE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADEL	Giant Romero SL
PEDALER	N/A
DRIVLINAN	
VÄXLAR	Shimano SLX M-7100, I-Spec EV, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	Shimano SLX M-7100, Shadow +
BROMSAR	Shimano BR-MT520, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BROMSSPAKAR	Shimano Deore BL-MT501
KASSETT	Shimano SLX M7100, 10x51
KEDJA	KMC X-12
VEVPARTI	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BROMSREGLAGE	Shimano Press Fit

HJUL	
FÄLGAR	Giant TRA WheelSystem, alloy, hollow rim wall construction, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NAV	[F] Giant Alloy, 6 Bolt [R] TRA HE, Alloy, 72 Pawl Driver, 6 bolt
EKRAR	Sapim, 28, straight pull, DBL Technology
DÄCK	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Price: 56 490,00 kr

GEOMETRY

RAM	M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Längd sadelrör (mm)	425			450			475		
Seat Post Insertion Depth (mm)	305			330			355		
Vinkel sadelrör	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Topprörets längd (mm)	602	601	600	624	623	622	657	656	655
Styrhuvud Längd (mm)	105			115			125		
Vinkel styrhuvud	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Gaffelvinkel (mm)	44			44			44		
Spår (mm)	134	131,3	128,5	133,9	131,3	128,5	133,9	131,3	128,6
Hjulbas (mm)	1222	1222	1221	1246	1246	1245	1281	1280	1280
Kedjestagslängd (mm)	440	439	438	440	439	438	440	439	438
Nedre fäste Drop (mm)	40	35	30	40	35	30	40	35	30
Stack (mm)	621	619	616	631	628	625	640	637	634
Reach (mm)	456	460	464	476	480	484	507	510	514
Stå över höjden (mm)	746	750	755	763	768	773	781	785	790
Styrets bredd (mm)	800			800			800		
Stamlängd (mm)	40			50			50		
Vevlängd (mm)	170			170			170		
Hjulstorlek	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All specifications listed are subject to change without notice.