

TRANCE X 2



SPECIFIKACE

RÁM	
VELIKOSTI	S, M, L, XL
BARVA	Metallic Black, Sandstorm
RÁM	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VIDLICE	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
TLUMIČ	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMPONENTY	
ŘÍDÍTKA	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIPY	Giant Tactal Pro Single Lock-On, 132x35mm
PŘEDSTAVEC	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEDOVKA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDLO	Giant Romero SL
PEDÁLY	N/A
OSAZENÍ	
ŘAZENÍ	Shimano Deore, 1x12
PŘESMYKAČ	N/A
PŘEHAZOVAČKA	Shimano Deore, Shadow +
BRZDY	Shimano BR-MT420, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRZDOVÉ PÁKY	Shimano Deore BL-MT401
KAZETA	Shimano Deore M6100, 10x51
ŘETĚZ	KMC X-12
KLIKY	Praxis Cadet HD M24, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
STŘED	Praxis, press fit

KOLA	
RÁFKY	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NÁBOJE	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
DRÁTY	Sapim, 28, J-bend
PLÁŠTĚ	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
DOPLŇKY	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GEOMETRIE

RÁM	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Délka sedlové trubky (mm)	400			425			450			475		
Max. zasunutí sedlovky (mm)	280			305			330			355		
Úhel sedlové trubky	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Délka horní trubky (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Délka hlavové trubky (mm)	100			105			115			125		
Úhel hlavové trubky	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Offset vidlice (mm)	44			44			44			44		
Trail (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	133,9	131,3	128,4
Rozvor (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	1279
Délka řetězové vzpěry (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Výška rámu od země (mm)	732	737	742	746	750	755	763	768	773	781	758	790
Šířka říditěk (mm)	800			800			800			800		
Délka představce (mm)	40			40			50			50		
Délka klik (mm)	165			170			170			170		
Rozměr kol	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Děláme vše pro to, aby veškeré údaje na tomto webu byly správné a aktuální. Přesto si ale musíme vyhradit právo na případné změny specifikací, barevného provedení a cen, a to bez předchozího upozornění. Děkujeme za pochopení.