

TRANCE X 2



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Tactical Grey
FRAME	ALUXX SL-grade Aluminium front and rear triangles, 140mm Maestro suspension, flip chip 3 position, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, integrated downtube storage, 55mm Chainline
FORK	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110mm Kabolt X thru-axle, 44mm offset
SHOCK	Fox Float Performance, 2 position, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, alloy, 20mm rise
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore, SL-M6200, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore, M7200, Shadow
BRAKES	TRP EVO Comp, hydraulic, TRP 2.3mm rotors [F]203mm, [R]180mm
BRAKE LEVERS	TRP EVO Comp
CASSETTE	Shimano Deore M6200, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet M24, 30T, Alloy Chainring, 55mm chainline S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	Praxis press fit

WHEELS	
RIMS	Giant TRA Hookless Tubeless ready Alloy, 29", 30mm inner width
HUBS	[F] Giant Boost Alloy Hub, 6 Bolt, Sealed Bearing, 28H [R] Giant Boost Alloy Hub, 6 Bolt, Sealed Bearing, HG, 28H
SPOKES	Sapim Race
TYRES	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO, TR [R] Maxxis Minion DHR II 29x2.4 WT, MaxxTerra, EXO, TR tubeless
EXTRAS	Tubeless prepared, 3M tailgate protector
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	34t

Price: \$4,499.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622	657	656	65
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3	
Wheelbase (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	43
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	63
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	51
Stand Over Height (mm)	732	737	742	746	750	755	763	768	773	781	785	79
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.