

# TRANCE X 2



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLOURS</b>	Metallic Black, Sandstorm
<b>FRAME</b>	ALUXX SL-grade aluminum front and rear triangles, 140mm Maestro suspension, flip chip - Maestro 3, flip chip - headset, 12x148mm thru-axle, integrated downtube storage
<b>FORK</b>	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
<b>SHOCK</b>	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, 20mm rise, alloy, 780x35mm
<b>GRIPS</b>	Giant Tactal Pro single lock-on
<b>STEM</b>	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
<b>SEATPOST</b>	Giant Contact Switch Adjustable, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L/XL: 170-200mm travel / 30.9 x 530mm
<b>SADDLE</b>	Giant Romero SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Deore, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano Deore, Shadow +
<b>BRAKES</b>	Shimano BR-MT420, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
<b>BRAKE LEVERS</b>	Shimano Deore BL-MT401
<b>CASSETTE</b>	Shimano Deore M6100, 10x51
<b>CHAIN</b>	KMC X-12
<b>CRANKSET</b>	Praxis Cadet HD M24, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
<b>BOTTOM BRACKET</b>	Praxis, press fit

WHEELS	
<b>RIMS</b>	Giant TRA 2 6061 alloy, sleevejoint, 30mm IW, 40mm OW, 21mm H, Wide Guard technology, [F] 29, [R] 29 *some bikes may be substituted: Giant AM 29, 6061 alloy, sleevejoint
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt, sealed [R] Giant MTB alloy, 6 bolt, 72t POE, 6-pawl, sealed *some bikes may be substituted: [F] alloy, loose, [R] alloy, sealed
<b>SPOKES</b>	Sapim Race j-bend *some bikes may be substituted: [F] Sapim Leader 14G, [R] Sapim Race 14G
<b>TIRES</b>	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
<b>EXTRAS</b>	tubeless prepared, 2.5" max tire size, 34t max chainring size, integrated down tube storage bag

**Suggested Retail Price (CDN): \$3,899.00**

## FRAME GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3	128.5
Wheelbase (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	1279
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Stand Over Height (mm)	732	737	742	746	750	755	763	768	773	781	758	759
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

All prices and specifications are subject to change without notice.