

TRANCE X 2



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Gloss Sandstorm
FRAME	ALUXX SL-grade aluminium front and rear triangles, 140mm Maestro suspension, flip chip - Maestro 3, flip chip - headset, 12x148mm thru-axle
FORK	Fox 36 Float Rhythm, GRIP damper, 44mm offset, 150mm, 15x110 Kabolt, custom tuned for Giant
SHOCK	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact TR35, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch Adjustable, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	Shimano Deore, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore
BRAKES	Shimano Deore BR-MT520, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore BL-MT401
CASSETTE	Shimano Deore, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet, 30t, 55mm chainline
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant AM 29" wheelset, AluXX wheelsystem, 30mm inner width
HUBS	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 30t POE (Points of Engagement), six-bolt, MicroSpline driver body
SPOKES	Sapim, 28, J-bend
TYRES	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAS	Factory tubeless set up
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	34t

Price: £3,299.00

GEOMETRY

FRAME	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	280	305	330	355
Seat Tube Angle	76.8° 77.2° 77.5°	76.8° 77.2° 77.5°	76.8° 77.2° 77.5°	76.8° 77.2° 77.5°
Top Tube Length (mm)	571 570 569	602 601 600	624 623 622	657 656 655
Head Tube Length (mm)	100	105	115	125
Head Tube Angle	64.4° 64.8° 65.1°	64.4° 64.8° 65.1°	64.4° 64.8° 65.1°	64.4° 64.8° 65.1°
Fork Rake (mm)	44	44	44	44
Trail (mm)	134.1 131.3 128.4	134 131.3 128.5	133.9 131.3 128.5	133.9 131.3 128.5
Wheelbase (mm)	1190 1190 1189	1222 1222 1221	1246 1246 1245	1281 1280 1279
Chain Stay Length (mm)	440 439 438	440 439 438	440 439 438	440 439 438
Bottom Bracket Drop (mm)	40 35 30	40 35 30	40 35 30	40 35 30
Stack (mm)	617 614 611	621 619 616	631 628 625	640 637 634
Reach (mm)	426 430 434	456 460 464	476 480 484	507 510 514
Stand Over Height (mm)	732 737 742	746 750 755	763 768 773	781 785 790
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.