

# TRANCE X 2



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLORS</b>	Metallic Black
<b>FRAME</b>	ALUXX SL-Grade aluminium front and rear triangles, 140mm Maestro suspension, flip chip 3 position, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, integrated downtube storage, 55mm Chainline
<b>FORK</b>	Fox 36 Float Rhythm, Grip, 44mm offset, 150mm travel, Boost 15x110 Kabolt X, 44mm offset, custom tuned for Giant
<b>SHOCK</b>	Fox Float Performance, 2 position lever, Trunnion, custom tuned for Giant
COMPONENTS	
<b>HANDLEBAR</b>	Giant Contact TR35, composite, 35mm
<b>GRIPS</b>	Giant Tactal Pro Single lock-on
<b>STEM</b>	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
<b>SEATPOST</b>	Giant Contact Switch AT dropper, adjustable travel, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
<b>SADDLE</b>	Giant Romero
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	Shimano Deore M6100, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	Shimano Deore-M6100
<b>BRAKES</b>	Shimano BR-M420, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
<b>BRAKE LEVERS</b>	Shimano BL-MT401
<b>CASSETTE</b>	Shimano M6100, 10x51
<b>CHAIN</b>	KMC X-12
<b>CRANKSET</b>	Praxis Cadet, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
<b>BOTTOM BRACKET</b>	Shimano, press fit

WHEELS	
<b>RIMS</b>	Giant TRA Hookless Tubeless ready Alloy 29 30mm inner width
<b>HUBS</b>	Giant TRX MTB Alloy Hub, 6 Bolt, 110x15 [F] / 148x12 SRAM XD Drive Body Pawl Driver (Pawl 36x2 T) Thru-axle [R]
<b>SPOKES</b>	Sapim Lite [R] Race [F]
<b>TIRES</b>	[F] Maxxis Minion DHF 29x2.5WT, 60 TPI, EXO, TR [R] Maxxis Dissector 29x2.4WT, 60 TPI, EXO, TR
<b>EXTRAS</b>	Tubeless prepared, max tyre size 2.5", max chainring size 34t

**Price: \$5,299.00**

## GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622	657	656	65
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3	
Wheelbase (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	43
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	63
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	51
Stand Over Height (mm)	732	737	742	746	750	755	763	768	773	781	758	79
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freighting and assembly costs.