

TRANCE X 2

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	S, M, L, XL
COLORES	Sandstorm
CUADRO	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
HORQUILLA	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMORTIGUADOR	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTES	
MANILLAR	Giant Contact TR35, alloy, 780x35mm, 20mm rise
PUÑOS	Giant Tactal Pro Single Lock-On, 132x35mm
POTENCIA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIJA DE SILLÍN	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SILLÍN	Giant Romero SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore, 1x12
DESVIADOR	N/A
CAMBIO TRASERO	Shimano Deore, Shadow +
FRENOS	Shimano BR-MT420, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
PALANCAS DE FRENOS	Shimano Deore BL-MT401
CASETTE	Shimano Deore M6100, 10x51
CADENA	KMC X-12
JGO. PLATOS Y BIELAS	Praxis Cadet HD M24, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
CAJA DE PEDALIER	Praxis, press fit

RUEDAS	
LLANTAS	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
BUJES	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
RADIOS	Sapim, 28, J-bend
CUBIERTAS	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Precio: 3.499,00 €

GEOMETRÍA

CUADRO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW
Longitud del tubo del sillín (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	280			305			330			355
Ángulo del tubo del sillín	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°
Longitud del tubo superior (mm) (mm)	571	570	569	602	601	600	624	623	622	657
Longitud del tubo de dirección (mm) (mm)	100			105			115			125
Ángulo del tubo de dirección	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°
Inclinación de la horquilla (mm)	44			44			44			44
Trail (mm) (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	133
Distancia entre ejes (mm) (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	128
Longitud de la vaina (mm) (mm)	440	439	438	440	439	438	440	439	438	440
Caída del eje de pedalier (mm) (mm)	40	35	30	40	35	30	40	35	30	40
Stack (mm) (mm)	617	614	611	621	619	616	631	628	625	640
Reach (mm) (mm)	426	430	434	456	460	464	476	480	484	507
Altura del suelo al tubo (mm) (mm)	732	737	742	746	750	755	763	768	773	781
Ancho del manillar (mm) (mm)	800			800			800			800
Longitud de la potencia (mm) (mm)	40			40			50			50
Longitud de las bielas (mm) (mm)	165			170			170			170
Tamaño de ruedas	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.