

TRANCE X 2



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Sandstorm
CADRE	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FOURCHE	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMORTISSEUR	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact TR35, alloy, 780x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single Lock-On, 132x35mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLE	Giant Romero SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	Shimano Deore, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano Deore, Shadow +
FREINS	Shimano BR-MT420, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
LEVIER DE FREIN	Shimano Deore BL-MT401
CASSETTE	Shimano Deore M6100, 10x51
CHAÎNE	KMC X-12
PÉDALIER	Praxis Cadet HD M24, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOITIER DE PÉDALIER	Praxis, press fit

ROUES	
JANTES	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
MOYEUX	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
RAYONS	Sapim, 28, J-bend
PNEUS	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 3 500,00 €

GÉOMÉTRIE

CADRE	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Longueur de tube de selle (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	280	305	330	355
Angle de tube de selle	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°
Longueur du tube supérieur (mm)	571 570 569	602 601 600	624 623 622	657 656 655
Longueur du tube de direction (mm)	100	105	115	125
Angle du tube de direction	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°
Déport de fourche (mm)	44	44	44	44
Trail (mm)	134,1 131,3 128,4	134 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5
Empattement (mm)	1190 1190 1189	1222 1222 1221	1246 1246 1245	1281 1281 1280
Longueur des bases (mm)	440 439 438	440 439 438	440 439 438	440 439 438
Drop du boîtier de pédalier (mm)	40 35 30	40 35 30	40 35 30	40 35 30
Stack (mm)	617 614 611	621 619 616	631 628 625	640 637 634
Reach (mm)	426 430 434	456 460 464	476 480 484	507 510 514
Hauteur en statique (mm)	732 737 742	746 750 755	763 768 773	781 785 790
Largeur de cintre (mm)	800	800	800	800
Longueur de potence (mm)	40	40	50	50
Longueur des manivelles (mm)	165	170	170	170
Diamètre des roues	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.