

TRANCE X 2



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Metallic Black, Sandstorm
TELAIO	ALUXX SL-Grade Aluminum front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORCELLA	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMMORTIZZATORE	Fox Float Performance, 185/52.5, custom tuned for Giant
COMPONENTISTICA	
MANUBRIO	Giant Contact TR35, alloy, 780x35mm, 20mm rise
MANOPOLE	Giant Tactal Pro Single Lock-On, 132x35mm
ATTACCO MANUBRIO	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
REGGISELLA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLA	Giant Romero SL
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	Shimano Deore, Shadow +
FRENI	Shimano BR-MT420, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
COMANDI FRENO	Shimano Deore BL-MT401
PACCO PIGNONI	Shimano Deore M6100, 10x51
CATENA	KMC X-12
GUARNITURA	Praxis Cadet HD M24, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRALE	Praxis, press fit

RUOTE	
CERCHI	Giant AM whellset
MOZZI	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
RAGGI	Sapim, 28, J-bend
COPERTONI	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRA	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Prezzo: 3.499,00 €

GEOMETRIA

TELAIO	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Lunghezza Tubo Sella (mm)	400	425	450	475
Profondità inserimento reggisella (mm)	280	305	330	355
Angolo Tubo Sella	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°
Lunghezza Tubo Orizzontale (mm)	571 570 569	602 601 600	624 623 622	657 656 655
Lunghezza Tubo Sterzo (mm)	100	105	115	125
Angolo Sterzo	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°
Rake Forcella (mm)	44	44	44	44
Avancorsa (mm)	134,1 131,3 128,4	134 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5
Interasse (mm)	1190 1190 1189	1222 1222 1221	1246 1246 1245	1281 1281 1280
Lunghezza Carro Posteriore (mm)	440 439 438	440 439 438	440 439 438	440 439 438
Drop Movimento Centrale (mm)	40 35 30	40 35 30	40 35 30	40 35 30
Stack (mm)	617 614 611	621 619 616	631 628 625	640 637 634
Reach (mm)	426 430 434	456 460 464	476 480 484	507 511 515
Altezza stand over (mm)	732 737 742	746 750 755	763 768 773	781 786 791
Larghezza Manubrio c/c (mm)	800	800	800	800
Lunghezza Attacco Manubrio (mm)	40	40	50	50
Lunghezza Pedivella (mm)	165	170	170	170
Dimensione Ruote	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.