



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Aged Denim/Snow Drift
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 145mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle
VILICE	Fox 36 Rhythm, GRIP damper, 37mm offset, 160mm, 15x110 Kabolt, custom tuned for Giant
AMORTIZER	Fox Float DPS Performance, 185/55, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SL TR35, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm
SEDEŽ	Giant Romero
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM NX Eagle, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM NX Eagle
ZAVORE	Shimano Deore BR-MT520, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	Shimano Deore BL-MT501
VERIŽNIK	SRAM NX Eagle, 11x50
VERIGA	SRAM GX Eagle
GONILKE Z VERIŽNIKI	TruVativ Descendent 6k Eagle, 32t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant AM 27.5, alloy
PESTA	alloy, sealed bearing
NAPERE	Sapim
PLAŠČI	[F] Maxxis Assegai 27.5x2.6, 3C MaxxTerra, EXO, TR [R] Maxxis Minion DHRII 27.5x2.6, 3C MaxxTerra, EXO, TR, tubeless
DODATKI	tubeless prepared, 2.6" max tire size, 34t max chainring size

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	420		430		465		496	
Kot sedežne cevi	77,2° 78,0°		76,3° 77,0°		76,3° 77,0°		76,3° 77,0°	
Top Tube Length (mm)	562	560	595	593	622	620	649	647
Višina glave okvirja (mm)	95		105		115		125	
Krmilni kot	63,7° 64,5°		63,8° 64,5°		63,8° 64,5°		63,8° 64,5°	
Zamik vpetja osi (mm)	37		37		37		37	
Trail (mm)	138	132	138	132	138	132	138	132
Medosna razdalja (mm)	1179	1177	1203	1202	1233	1231	1262	1260
Dolžina cevi ob verigi (mm)	433	430	433	430	433	430	433	430
Bottom Bracket Drop (mm)	30	20	30	20	30	20	30	20
Oddaljenost zgornje cevi od gonilne osi (mm)	596	590	605	599	614	608	623	617
Doseg (mm)	427	435	447	455	472	480	497	505
Višina zgornje cevi (mm)	709	718	714	723	740	750	762	772
Širina krmila (mm)	800		800		800		800	
Dolžina opore krmila (mm)	40		40		50		50	
Dolžina gonilke (mm)	165		170		170		170	
Velikost obročnikov	27,5"		27,5"		27,5"		27,5"	

Vse navedene specifikacije se lahko spremenijo brez obvestila.