

TRANCE X 29 1

GIANT



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Panther / Phantom Green / Chrome, Chameleon Blue / Black / Chrome
CADRE	ALUXX SL-Grade Aluminum front and rear triangles, 135mm Maestro suspension, flip chip, 12x148mm thru-axle
FOURCHE	Fox 36 Float Performance, 150mm Travel, Grip Damper, Boost 15x110 Kabolt X, Tapered
AMORTISSEUR	Fox Float DPS Performance, 185/55, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact TR35, 780x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 440mm L: 170mm travel / 30.9 x 450mm XL: 170mm travel / 30.9 x 450mm
SELLE	Giant Romero
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	Shimano SLX SL-M7100, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano SLX RD-M7100
FREINS	Shimano Deore BR-MT520, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
LEVIER DE FREIN	Shimano Deore BL-MT501
CASSETTE	Shimano SLX, 10x51
CHAÎNE	KMC X-12
PÉDALIER	Shimano M511, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOITIER DE PÉDALIER	Shimano, press fit

ROUES	
JANTES	Giant AM 29, alloy
MOYEUX	alloy, sealed bearing
RAYONS	Sapim
PNEUS	[F] Maxxis Minion DHF 29x2.5 WT, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 TPI, 3C Max Terra, EXO, TR
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 4 000,00 €

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	430	430	465	465	496	496		
Angle de tube de selle	77,2°	77,9°	77,2°	77,9°	77,2°	77,9°	77,2°	77,9°
Longueur du tube supérieur (mm)	566 564	597 595	629 627	656 654				
Longueur du tube de direction (mm)	95	100	110	120				
Angle du tube de direction	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°	65,5° 66,2°				
Déport de fourche (mm)	44	44	44	44				
Trail (mm)	125,1 119,5	125,1 119,5	125,1 119,7	125,1 119,5				
Empattement (mm)	1173 1172	1205 1204	1239 1238	1268 1266				
Longueur des bases (mm)	438 435	438 435	438 435	438 435				
Drop du boîtier de pédalier (mm)	40 30	40 30	40 30	40 30				
Stack (mm)	617 611	621 615	631 624	640 634				
Reach (mm)	426 434	456 464	486 494	511 519				
Hauteur en statique (mm)	735 743	729 738	754 763	777 786				
Largeur de cintre (mm)	780	780	780	780				
Longueur de potence (mm)	40	40	50	50				
Longueur des manivelles (mm)	165	170	170	170				
Diamètre des roues	29"	29"	29"	29"				

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.