

TRANCE X 29 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Panther / Phantom Green / Chrome, Chameleon Blue / Black / Chrome
OKVIR	ALUXX SL-Grade Aluminum front and rear triangles, 135mm Maestro suspension, flip chip, 12x148mm thru-axle
VILICE	Fox 36 Float Performance, FIT4, 44mm offset, 150mm, 15x110 Kabolt, custom tuned for Giant
AMORTIZER	Fox Float DPS Performance, 185/55, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact TR35, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 440mm L: 170mm travel / 30.9 x 450mm XL: 170mm travel / 30.9 x 450mm
SEDEŽ	Giant Romero
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano SLX SL-M7100, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano SLX RD-M7100
ZAVORE	Tektro HD-M745 Orion, 4-piston, hydraulic disc [F]203mm, [R]180mm
ZAVORNE ROČICE	Tektro HD-M745 Orion
VERIŽNIK	Shimano SLX, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Shimano M511, 30t S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	Shimano, press fit

OBROČNIKI	
OBROČI	Giant AM 29, alloy
PESTA	alloy, sealed bearing
NAPERE	Sapim
PLAŠČI	[F] Maxxis Minion DHF 29x2.5 WT, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 TPI, 3C Max Terra, EXO, TR
DODATKI	tubeless prepared, 2.5" max tire size, 34t max chainring size

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	430		430		465		496	
Kot sedežne cevi	77,2° 77,9°		77,2° 77,9°		77,2° 77,9°		77,2° 77,9°	
Top Tube Length (mm)	566 564		597 595		629 627		656 654	
Višina glave okvirja (mm)	95		100		110		120	
Krmilni kot	65,5° 66,2°		65,5° 66,2°		65,5° 66,2°		65,5° 66,2°	
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	125,1 119,5		125,1 119,5		125,1 119,7		125,1 119,5	
Medosna razdalja (mm)	1173 1172		1205 1204		1239 1238		1268 1266	
Dolžina cevi ob verigi (mm)	438 435		438 435		438 435		438 435	
Bottom Bracket Drop (mm)	40 30		40 30		40 30		40 30	
Oddaljenost zgornje cevi od gonilne osi (mm)	617 611		621 615		631 624		640 634	
Doseg (mm)	426 434		456 464		486 494		511 519	
Višina zgornje cevi (mm)	735 743		729 738		754 763		777 786	
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	40		40		50		50	
Dolžina gonilke (mm)	165		170		170		170	
Velikost obročnikov	29"		29"		29"		29"	

Vse navedene specifikacije se lahko spremenijo brez obvestila.