

TRANCE X ADVANCED 0



SPECS

FRAME	
SIZES	Select Sizes Available: M, L
COLORS	Blue Dragonfly/Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORK	Fox 36 Factory, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float X Factory, two-position LSC adjust, 185/52.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR Trail Integrated, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
STEM	Giant Contact Integrated SLR Trail S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XO Eagle AXS, T-Type
BRAKES	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XO, T-Type, 10x52
CHAIN	SRAM XO, T-Type
CRANKSET	SRAM XO, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
HUBS	Giant TRX 0 29 Carbon WheelSystem
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Recommended Retail Price: \$8,000.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (inch)	15.7			16.7			17.7			18.7		
Seat Post Insertion Depth (inch)	11			12			13			14		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°
Top Tube Length (inch)	22.5	22.4	22.4	23.7	23.7	23.6	24.6	24.5	24.5	25.9	25.8	25.8
Head Tube Length (inch)	3.9			4.1			4.5			4.9		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°
Fork Rake (inch)	1.7			1.7			1.7			1.7		
Trail (inch)	5.3	5.2	5	5.3	5.2	5	5.2	5.2	5	5.2	5.2	5
Wheelbase (inch)	46.9	46.9	46.8	48.1	48.1	48.1	49.1	49.1	49	50.4	50.4	50.4
Chain Stay Length (inch)	17.3	17.3	17.2	17.3	17.3	17.2	17.3	17.3	17.2	17.3	17.3	17.2
Bottom Bracket Drop (inch)	1.6	1.4	1.2	1.6	1.4	1.2	1.6	1.4	1.2	1.6	1.4	1.2
Stack (inch)	24.3	24.2	24.1	24.4	24.4	24.3	24.8	24.7	24.6	25.2	25.1	25
Reach (inch)	16.8	16.9	17.1	18	18.1	18.3	18.7	18.9	19.1	20	20.1	20.2
Stand Over Height (inch)	28.9	29	29.2	29	29.2	29.4	29.7	29.9	30	29.6	29.8	30
Handlebar Width (inch)	31.5			31.5			31.5			31.5		
Stem Length (inch)	1.6			1.6			2			2		
Crank Length (inch)	6.5			6.7			6.7			6.7		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*