

TRANCE X ADVANCED 0

GIANT



TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Blue Dragonfly/Chrome
CADRE	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FOURCHE	Fox 36 Factory, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
AMORTISSEUR	Fox Float X Factory, two-position LSC adjust, 185/52.5, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact SLR Trail Integrated, composite, 800x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single Lock-On, 132x35mm
POTENCE	Giant Contact Integrated SLR Trail S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLE	Giant Romero SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES	SRAM AXS Pod, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM XO Eagle AXS, T-Type
FREINS	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
LEVIERS DE FREIN	Shimano Deore XT BL-M8100
CASSETTE	SRAM XO, T-Type, 10x52
CHAÎNE	SRAM XO, T-Type
PÉDALIER	SRAM XO, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOYEUX	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, XD driver body
RAYONS	Sapim, 28, straight pull, DBL Technology
PNEUS	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles

Prix Public Conseillé: 8 500,00 €

GÉOMÉTRIE

CADRE	S	M	L	XL
Longueur de tube de selle (mm)	LOW MID HIGH 400	LOW MID HIGH 425	LOW MID HIGH 450	LOW MID HIGH 475
Seat Post Insertion Depth (mm)	280	305	330	355
Angle de tube de selle	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°
Longueur du tube supérieur (mm)	571 570 569	602 601 600	624 623 622	657 656
Longueur du tube de direction (mm)	100	105	115	125
Angle du tube de direction	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°
Déport de fourche (mm)	44	44	44	44
Trail (mm)	134,1 131,3 128,4	134 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5
Empattement (mm)	1190 1190 1189	1222 1222 1221	1246 1246 1245	1281 1281 1280
Longueur des bases (mm)	440 439 438	440 439 438	440 439 438	440 439 438
Drop du boîtier de pédalier (mm)	40 35 30	40 35 30	40 35 30	40 35 30
Stack (mm)	617 614 611	621 619 616	631 628 625	640 637
Reach (mm)	426 430 434	456 460 464	476 480 484	507 510
Hauteur en statique (mm)	733 737 742	737 741 746	754 759 763	752 757
Largeur de cintre (mm)	800	800	800	800
Longueur de potence (mm)	40	40	50	50
Longueur des manivelles (mm)	165	170	170	170
Diamètre des roues	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.