

TRANCE X ADVANCED 0



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Blue Dragonfly/Chrome
TELAIO	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORCELLA	Fox 36 Factory, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
AMMORTIZZATORE	Fox Float X Factory, two-position LSC adjust, 185/52.5, custom tuned for Giant
COMPONENTISTICA	
MANUBRIO	Giant Contact SLR Trail Integrated, composite, 800x35mm, 20mm rise
MANOPOLE	Giant Tactal Pro Single Lock-On, 132x35mm
ATTACCO MANUBRIO	Giant Contact Integrated SLR Trail S:40mm, M:40mm, L:50mm, XL:50mm
REGGISELLA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLA	Giant Romero SL
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	SRAM AXS Pod, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	SRAM XO Eagle AXS, T-Type
FRENI	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
COMANDI FRENO	Shimano Deore XT BL-M8100
PACCO PIGNONI	SRAM XO, T-Type, 10x52
CATENA	SRAM XO, T-Type
GUARNITURA	SRAM XO, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRALE	SRAM DUB, press fit

RUOTE	
CERCHI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOZZI	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, XD driver body
RAGGI	Sapim, 28, straight pull, DBL Technology
COPERTONI	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRA	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Prezzo: 8.949,00 €

GEOMETRIA

TELAIO	S			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Lunghezza Tubo Sella (mm)	400			450			475		
Profondità inserimento reggisella (mm)	280			330			355		
Angolo Tubo Sella	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Lunghezza Tubo Orizzontale (mm)	571	570	569	624	623	622	657	656	655
Lunghezza Tubo Sterzo (mm)	100			115			125		
Angolo Sterzo	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Rake Forcella (mm)	44			44			44		
Avancorsa (mm)	134,1	131,3	128,4	133,9	131,3	128,5	133,9	131,3	128,6
Interasse (mm)	1190	1190	1189	1246	1246	1245	1281	1280	1280
Lunghezza Carro Posteriore (mm)	440	439	438	440	439	438	440	439	438
Drop Movimento Centrale (mm)	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	631	628	625	640	637	634
Reach (mm)	426	430	434	476	480	484	507	510	514
Altezza stand over (mm)	733	737	742	754	759	763	752	757	762
Larghezza Manubrio c/c (mm)	800			800			800		
Lunghezza Attacco Manubrio (mm)	40			50			50		
Lunghezza Pedivella (mm)	165			170			170		
Dimensione Ruote	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.