

TRANCE X ADVANCED 0



SPECS

FRAME	
SIZES	S, M
COLORS	ブルードラゴンフライ
FRAME	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORK	Fox 36 Factory, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float X Factory, two-position LSC adjust, 185/52.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR Trail Integrated, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
STEM	Giant Contact Integrated SLR Trail S:40mm, M:40mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm
SADDLE	Giant Romero SL
PEDALS	N/A
HEADSET	FSA ORBIT 1.5 ZS Sealed Cartridge 1-1/8"-1-1/2"
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM XO Eagle AXS, T-Type
BRAKES	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XO, T-Type, 10x52
CHAIN	SRAM XO, T-Type
CRANKSET	SRAM XO, T-Type, 30t, 55mm chainline S:165mm, M:170mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
HUBS	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, XD driver body
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	チューブレスタイヤ、シーラント、フレームストレージバッグ
LIMITS	
MAX TIRE CLEARANCE	2.5"
MAX CHAINRING SIZE	34t

Price: ¥1,100,000

GEOMETRY

FRAME	S			M		
	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425		
Seat Post Insertion Depth (mm)	280			305		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°
Top Tube Length (mm)	571	570	569	602	601	600
Head Tube Length (mm)	100			105		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°
Fork Rake (mm)	44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5
Wheelbase (mm)	1190	1190	1189	1222	1222	1221
Chain Stay Length (mm)	440	439	438	440	439	438
Bottom Bracket Drop (mm)	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616
Reach (mm)	426	430	434	456	460	464
Stand Over Height (mm)	733	737	742	737	741	746
Handlebar Width (mm)	800			800		
Stem Length (mm)	40			40		
Crank Length (mm)	165			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]		

製品仕様は改良、部品供給上の都合により予告なしに変更する場合があります。あらかじめご了承ください。製品重量は個体差により実際と若干異なる場合がございます。また、Giant Premium Model（カーボンバイクおよびダブルサスペンションMTB）は、GPD(Giant Premium Dealer)のみで販売しております。対象販売店は、[店舗検索](#)にてご確認ください。