

# TRANCE X ADVANCED 0



## SPECS

| QUADRO                |                                                                                                                                                                                                                                                    |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| TAMANHOS              | S, M, L, XL                                                                                                                                                                                                                                        |
| CORES                 | Blue Dragonfly                                                                                                                                                                                                                                     |
| QUADRO                | Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts |
| FORQUILHA             | Fox 36 Factory, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset                                                                                                                                                                                 |
| AMORTECEDORES         | Fox Float X Factory, two-position LSC adjust, 185/52.5, custom tuned for Giant                                                                                                                                                                     |
| COMPONENTES           |                                                                                                                                                                                                                                                    |
| GUIADOR               | Giant Contact SLR Trail Integrated, composite, 800x35mm, 20mm rise                                                                                                                                                                                 |
| PUNHOS                | Giant Tactal Pro Single Lock-On, 132x35mm                                                                                                                                                                                                          |
| AVANÇO                | Giant Contact Integrated SLR Trail S:40mm, M:40mm, L:50mm, XL:50mm                                                                                                                                                                                 |
| ESPIGÃO DE SELIM      | Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm                                                                     |
| SELIM                 | Giant Romero SL                                                                                                                                                                                                                                    |
| PEDAIS                | N/A                                                                                                                                                                                                                                                |
| TRANSMISSÃO           |                                                                                                                                                                                                                                                    |
| MANETES               | SRAM AXS Pod, 1x12                                                                                                                                                                                                                                 |
| DESVIADOR DIANTEIRO   | N/A                                                                                                                                                                                                                                                |
| DESVIADOR TRASEIRO    | SRAM XO Eagle AXS, T-Type                                                                                                                                                                                                                          |
| TRAVÕES               | Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm                                                                                                                                                         |
| MANÍPULOS DOS TRAVÕES | Shimano Deore XT BL-M8100                                                                                                                                                                                                                          |
| CASSETE               | SRAM XO, T-Type, 10x52                                                                                                                                                                                                                             |
| CORRENTE              | SRAM XO, T-Type                                                                                                                                                                                                                                    |
| CONJUNTO PEDALEIRO    | SRAM XO, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm                                                                                                                                                                           |
| MOVIMENTO CENTRAL     | SRAM DUB, press fit                                                                                                                                                                                                                                |

| RODAS  |                                                                                                                                    |
|--------|------------------------------------------------------------------------------------------------------------------------------------|
| AROS   | Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology                    |
| CUBOS  | [F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, XD driver body                        |
| RAIOS  | Sapim, 28, straight pull, DBL Technology                                                                                           |
| PNEUS  | [F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless |
| EXTRAS | tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection           |

Preço: 7 449,00 €

## GEOMETRIA

| QUADRO                              | S           |       |       | M           |       |       | L           |       |       | XL      |
|-------------------------------------|-------------|-------|-------|-------------|-------|-------|-------------|-------|-------|---------|
|                                     | LOW         | MID   | HIGH  | LOW         | MID   | HIGH  | LOW         | MID   | HIGH  |         |
| Comprimento do tubo do assento (mm) | 400         |       |       | 425         |       |       | 450         |       |       | 475     |
| Seat Post Insertion Depth (mm)      | 280         |       |       | 305         |       |       | 330         |       |       | 355     |
| Ângulo do tubo do assento           | 76,8°       | 77,2° | 77,5° | 76,8°       | 77,2° | 77,5° | 76,8°       | 77,2° | 77,5° | 76,8°   |
| Comprimento do tubo superior (mm)   | 571         | 570   | 569   | 602         | 601   | 600   | 624         | 623   | 622   | 657     |
| Comprimento do tubo principal (mm)  | 100         |       |       | 105         |       |       | 115         |       |       | 125     |
| Ângulo do tubo principal            | 64,4°       | 64,8° | 65,1° | 64,4°       | 64,8° | 65,1° | 64,4°       | 64,8° | 65,1° | 64,4°   |
| Garfo ancinho (mm)                  | 44          |       |       | 44          |       |       | 44          |       |       | 44      |
| Trilha (mm)                         | 134,1       | 131,3 | 128,4 | 134         | 131,3 | 128,5 | 133,9       | 131,3 | 128,5 | 133,9   |
| distância entre eixos (mm)          | 1190        | 1190  | 1189  | 1222        | 1222  | 1221  | 1246        | 1246  | 1245  | 1281    |
| Comprimento Chain Stay (mm)         | 440         | 439   | 438   | 440         | 439   | 438   | 440         | 439   | 438   | 440     |
| Suporte inferior (mm)               | 40          | 35    | 30    | 40          | 35    | 30    | 40          | 35    | 30    | 40      |
| Pilha (mm)                          | 617         | 614   | 611   | 621         | 619   | 616   | 631         | 628   | 625   | 640     |
| Alcançar (mm)                       | 426         | 430   | 434   | 456         | 460   | 464   | 476         | 480   | 484   | 507     |
| Altura do standover (mm)            | 733         | 737   | 742   | 737         | 741   | 746   | 754         | 759   | 763   | 752     |
| Largura do guidão (mm)              | 800         |       |       | 800         |       |       | 800         |       |       | 800     |
| Comprimento da haste (mm)           | 40          |       |       | 40          |       |       | 50          |       |       | 50      |
| Comprimento da Manivela (mm)        | 165         |       |       | 170         |       |       | 170         |       |       | 170     |
| Tamanho da roda                     | [F] 29" [R] |       |       | [F] 29" [R] |       |       | [F] 29" [R] |       |       | [F] 29" |

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.