



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Arctic Light/Chrome
RAHMEN	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
GABEL	Fox 36 Performance Elite, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
DÄMPFER	Fox Float X Performance Elite, two-position LSC adjust, 185/52.5, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact SL TR35, alloy, 780x35mm, 20mm rise
GRIFFE	Giant Tactal Pro Single Lock-On, 132x35mm
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SATTELSTÜTZE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SATTEL	Giant Romero SL
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM AXS Pod, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle AXS, T-Type
BREMSSEN	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BREMSHEBEL	Shimano Deore XT BL-M8100
KASSETTE	SRAM GX, T-Type, 10x52
KETTE	SRAM GX, T-Type
KURBEL	SRAM GX, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	SRAM DUB, Press Fit

LAUFRÄDER	
FELGEN	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NABE	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
SPEICHEN	Sapim, 28, straight pull, DBL Technology
REIFEN	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GEOMETRIEDATEN

RAHMEN	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Sitzrohrwinkel	76.8° 77.2° 77.5°			76.8° 77.2° 77.5°			76.8° 77.2° 77.5°			76.8° 77.2° 77.5°		
Oberrohrlänge (mm)	571 570 569			602 601 600			624 623 622			657 656 655		
Steuerrohr-Länge (mm)	100			105			115			125		
Steuerrohr-Winkel	64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 64.8°		
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	134.1 131.3 128.4			134 131.3 128.5			133.9 131.3 128.5			133.9 131.3 128.5		
Radstand (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245			1281 1280 1280		
Kettenstreben-Länge (mm)	440 439 438			440 439 438			440 439 438			440 439 438		
Tretlager-Höhe (mm)	40 35 30			40 35 30			40 35 30			40 35 30		
Stack (mm)	617 614 611			621 619 616			631 628 625			640 637 634		
Reach (mm)	426 430 434			456 460 464			476 480 484			507 510 514		
Überstandshöhe (mm)	733 737 742			737 741 746			754 759 763			752 757 761		
Lenkerbreite (mm)	800			800			800			800		
Vorbaulänge (mm)	40			40			50			50		
Kurbellänge (mm)	165			170			170			170		
Radgrösse	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Spezifikations-, Preis- und Farbänderungen vorbehalten.