

TRANCE X ADVANCED 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Abyss Teal
FRAME	Advanced-Grade Composite front and rear triangles, UDH, 140mm Maestro suspension, flip chip 3 position, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, integrated downtube storage, 55mm Chainline
FORK	Fox 36 Factory, 150mm, GRIP X damper, 15x110mm Kabolt X thru-axle, 44mm offset
SHOCK	Fox Float X Factory, 2 position, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SL TR35, alloy, 20mm rise
GRIPS	Giant Tactal Pro Single lock-on
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle Transmission AXS
BRAKES	TRP EVO Pro, hydraulic, TRP 2.3mm rotors [F]203mm, [R]180mm
BRAKE LEVERS	TRP EVO Pro
CASSETTE	SRAM XS-1275 Transmission, 10x52
CHAIN	SRAM GX Transmission
CRANKSET	SRAM GX Transmission, 30t, 55mm chainline S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	Giant TRX Hookless Tubeless ready Carbon, 29", 30mm inner width
HUBS	[F] Giant TRX MTB Alloy Hub, 6 Bolt, 28H [R] Giant TRX MTB Alloy Hub, SRAM XD Drive Body Pawl Driver (Pawl 36x2 T), 28H
SPOKES	Sapim Laser
TYRES	[F] Maxxis Assegai 29x2.5 WT, MaxxTerra, EXO, TR [R] Maxxis Minion DHR II 29x2.4 WT, MaxxTerra, EXO, TR tubeless
EXTRAS	Tubeless prepared, chain guide, 3M tailgate protector
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	34t

Price: \$8,999.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622	657	656	65
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3	
Wheelbase (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	
Chain Stay Length (mm)	440	439	438	440	439	438	440	439	438	440	439	43
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	63
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	51
Stand Over Height (mm)	733	737	742	737	741	746	754	759	763	752	757	76
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.