

TRANCE X ADVANCED 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Gloss Arctic Light/Chrome
FRAME	Advanced-grade composite front and rear triangles, 140mm Maestro suspension, flip chip - Maestro 3, flip chip - headset, 12x148mm thru-axle
FORK	Fox 36 Performance Elite, GRIP2 damper, 44mm offset, 150mm, 15x110 Kabolt X, custom tuned for Giant
SHOCK	Fox Float X Performance Elite, 185/52.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SLR TR35, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Giant Contact Switch Adjustable, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	PEDALS NOT SUPPLIED
DRIVETRAIN	
SHIFTERS	SRAM AXS, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle Transmission AXS
BRAKES	Shimano Deore XT BR-MT8120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX-1275, 10x52
CHAIN	SRAM GX Eagle
CRANKSET	SRAM GX, 30t, 55mm chainline
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	Giant TRX, 29" hookless carbon wheelsystem, 30mm IW, 40mm OW, 22mm H, 72t POE, 28 SP spokes, DBL technology, XD driver body
HUBS	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
SPOKES	Sapim, 28, straight pull, DBL Technology
TYRES	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	Factory tubeless set up, 3M tailgate protector
LIMITS	
MAX TYRE CLEARANCE	2.5"
MAX CHAINRING SIZE	34t

Price: £5,999.00

GEOMETRY

FRAME	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76.8° 77.2° 77.5°			76.8° 77.2° 77.5°			76.8° 77.2° 77.5°			76.8° 77.2° 77.5°		
Top Tube Length (mm)	571 570 569			602 601 600			624 623 622			657 656 655		
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 65.1°			64.4° 64.8° 65.1°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134.1 131.3 128.4			134 131.3 128.5			133.9 131.3 128.5			133.9 131.3 128.5		
Wheelbase (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245			1281 1280 1279		
Chain Stay Length (mm)	440 439 438			440 439 438			440 439 438			440 439 438		
Bottom Bracket Drop (mm)	40 35 30			40 35 30			40 35 30			40 35 30		
Stack (mm)	617 614 611			621 619 616			631 628 625			640 637 634		
Reach (mm)	426 430 434			456 460 464			476 480 484			507 510 513		
Stand Over Height (mm)	733 737 742			737 741 746			754 759 763			752 757 761		
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.