TRANCE X ADVANCED 1



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Arctic Light/Chrome
FRAME	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORK	Fox 36 Performance Elite, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
SHOCK	Fox Float X Performance Elite, two-position LSC adjust, 185/52.5, custom tuned for Giant
COMPONENTS	
HANDLEBAR	Giant Contact SL TR35, alloy, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
STEM	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SEATPOST	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SADDLE	Giant Romero SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX Eagle AXS, T-Type
BRAKES	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX, T-Type, 10x52
CHAIN	SRAM GX, T-Type
CRANKSET	SRAM GX, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
HUBS	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
SPOKES	Sapim, 28, straight pull, DBL Technology
TIRES	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Price: ₹ 7,200.00

GEOMETRY

FRAME	S	M	L	XL
	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | HIGH	LOW | MID | H
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	280	305	330	355
Seat Tube Angle	76.8° | 77.2° | 77.5°	76.8° | 77.2° | 77.5°	76.8° | 77.2° | 77.5°	76.8° | 77.2° |
Top Tube Length (mm)	571 | 570 | 569	602 | 601 | 600	624 | 623 | 622	657 | 656 | 65
Head Tube Length (mm)	100	105	115	125
Head Tube Angle	64.4° | 64.8° | 65.1°	64.4° | 64.8° | 65.1°	64.4° | 64.8° | 65.1°	64.4° | 64.8° |
Fork Rake (mm)	44	44	44	44
Trail (mm)	134.1 | 131.3 | 128.4	134 | 131.3 | 128.5	133.9 | 131.3 | 128.5	133.9 | 131.3 |
Wheelbase (mm)	1190 | 1190 | 1189	1222 | 1222 | 1221	1246 | 1246 | 1245	1281 | 1280 |
Chain Stay Length (mm)	440 | 439 | 438	440 | 439 | 438	440 | 439 | 438	440 | 439 | 43
Bottom Bracket Drop (mm)	40 | 35 | 30	40 | 35 | 30	40 | 35 | 30	40 | 35 | 30
Stack (mm)	617 | 614 | 611	621 | 619 | 616	631 | 628 | 625	640 | 637 | 63
Reach (mm)	426 | 430 | 434	456 | 460 | 464	476 | 480 | 484	507 | 510 | 51
Stand Over Height (mm)	733 | 737 | 742	737 | 741 | 746	754 | 759 | 763	752 | 757 | 76
Handlebar Width (mm)	800	800	800	800
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	170	170	170
Wheel Size	[F] 29" [R	[F] 29" [R	[F] 29" [R	[F] 29" [R

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.