



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Arctic Light/Chrome
CADRE	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FOURCHE	Fox 36 Performance Elite, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
AMORTISSEUR	Fox Float X Performance Elite, two-position LSC adjust, 185/52.5, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact SL TR35, alloy, 780x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single Lock-On, 132x35mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLE	Giant Romero SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES DÉRAILLEUR	SRAM AXS Pod, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	SRAM GX Eagle AXS, T-Type
FREINS	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
LEVIER DE FREIN	Shimano Deore XT BL-M8100
CASSETTE	SRAM GX, T-Type, 10x52
CHAÎNE	SRAM GX, T-Type
PÉDALIER	SRAM GX, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
PÉDALIER	SRAM DUB, Press Fit

ROUES	
JANTES	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOYEUX	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
RAYONS	Sapim, 28, straight pull, DBL Technology
PNEUS	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GÉOMÉTRIE

CADRE	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Longueur de tube de selle (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Angle de tube de selle	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Longueur du tube supérieur (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Longueur du tube de direction (mm)	100			105			115			125		
Angle du tube de direction	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Déport de fourche (mm)	44			44			44			44		
Chasse (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5	133,9	131,3	128,5
Empattement (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1281	1280
Longueur des bases (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Hauteur du boîtier de pédalier (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Hauteur d'enjambement (mm)	733	737	742	737	741	746	754	759	763	752	757	761
Largeur de cintre (mm)	800			800			800			800		
Longueur de potence (mm)	40			40			50			50		
Longueur des manivelles (mm)	165			170			170			170		
Diamètre des roues	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Giant Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.