

TRANCE X ADVANCED 1



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Arctic Light/Chrome
TELAIO	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORCELLA	Fox 36 Performance Elite, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
AMMORTIZZATORE	Fox Float X Performance Elite, two-position LSC adjust, 185/52.5, custom tuned for Giant
COMPONENTISTICA	
MANUBRIO	Giant Contact SL TR35, alloy, 780x35mm, 20mm rise
MANOPOLE	Giant Tactal Pro Single Lock-On, 132x35mm
ATTACCO MANUBRIO	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
REGGISELLA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLA	Giant Romero SL
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	SRAM AXS Pod, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	SRAM GX Eagle AXS, T-Type
FRENI	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
COMANDI FRENO	Shimano Deore XT BL-M8100
PACCO PIGNONI	SRAM GX, T-Type, 10x52
CATENA	SRAM GX, T-Type
GUARNITURA	SRAM GX, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRALE	SRAM DUB, Press Fit

RUOTE	
CERCHI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
MOZZI	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
RAGGI	Sapim, 28, straight pull, DBL Technology
COPERTONI	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRA	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Prezzo: 7.199,00 €

GEOMETRIA

TELAIO	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Lunghezza Tubo Sella (mm)	400	425	450	475
Profondità inserimento reggisella (mm)	280	305	330	355
Angolo Tubo Sella	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°
Lunghezza Tubo Orizzontale (mm)	571 570 569	602 601 600	624 623 622	657 656 655
Lunghezza Tubo Sterzo (mm)	100	105	115	125
Angolo Sterzo	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°
Rake Forcella (mm)	44	44	44	44
Avancorsa (mm)	134,1 131,3 128,4	134 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5
Interasse (mm)	1190 1190 1189	1222 1222 1221	1246 1246 1245	1281 1281 1280
Lunghezza Carro Posteriore (mm)	440 439 438	440 439 438	440 439 438	440 439 438
Drop Movimento Centrale (mm)	40 35 30	40 35 30	40 35 30	40 35 30
Stack (mm)	617 614 611	621 619 616	631 628 625	640 637 634
Reach (mm)	426 430 434	456 460 464	476 480 484	507 511 515
Altezza stand over (mm)	733 737 742	737 741 746	754 759 763	752 756 760
Larghezza Manubrio c/c (mm)	800	800	800	800
Lunghezza Attacco Manubrio (mm)	40	40	50	50
Lunghezza Pedivella (mm)	165	170	170	170
Dimensione Ruote	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.