

TRANCE X ADVANCED 1



SPECS

QUADRO	
TAMANHOS	S, M, L, XL
CORES	Arctic Light/Chrome
QUADRO	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FORQUILHA	Fox 36 Performance Elite, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
AMORTECEDORES	Fox Float X Performance Elite, two-position LSC adjust, 185/52.5, custom tuned for Giant
COMPONENTES	
GUIADOR	Giant Contact SL TR35, alloy, 780x35mm, 20mm rise
PUNHOS	Giant Tactal Pro Single Lock-On, 132x35mm
AVANÇO	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
ESPIGÃO DE SELIM	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELIM	Giant Romero SL
PEDAIS	N/A
TRANSMISSÃO	
MANETES	SRAM AXS Pod, 1x12
DESVIADOR DIANTEIRO	N/A
DESVIADOR TRASEIRO	SRAM GX Eagle AXS, T-Type
TRAVÕES	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
MANÍPULOS DOS TRAVÕES	Shimano Deore XT BL-M8100
CASSETE	SRAM GX, T-Type, 10x52
CORRENTE	SRAM GX, T-Type
CONJUNTO PEDALEIRO	SRAM GX, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
MOVIMENTO CENTRAL	SRAM DUB, Press Fit

RODAS	
AROS	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
CUBOS	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
RAIOS	Sapim, 28, straight pull, DBL Technology
PNEUS	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

Preço: 6 149,00 €

GEOMETRIA

QUADRO	S			M			L			XL
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	
Comprimento do tubo do assento (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	280			305			330			355
Ângulo do tubo do assento	76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8°
Comprimento do tubo superior (mm)	571 570 569			602 601 600			624 623 622			657
Comprimento do tubo principal (mm)	100			105			115			125
Ângulo do tubo principal	64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4°
Garfo ancinho (mm)	44			44			44			44
Trilha (mm)	134,1 131,3 128,4			134 131,3 128,5			133,9 131,3 128,5			133,9
distância entre eixos (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245			1281
Comprimento Chain Stay (mm)	440 439 438			440 439 438			440 439 438			440
Suporte inferior (mm)	40 35 30			40 35 30			40 35 30			40 3
Pilha (mm)	617 614 611			621 619 616			631 628 625			640
Alcançar (mm)	426 430 434			456 460 464			476 480 484			507
Altura do standover (mm)	733 737 742			737 741 746			754 759 763			752
Largura do guidão (mm)	800			800			800			800
Comprimento da haste (mm)	40			40			50			50
Comprimento da Manivela (mm)	165			170			170			170
Tamanho da roda	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29'

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.