

TRANCE X ADVANCED 1



SPECS

CADRU	
MARIMI	S, M, L, XL
CULORI	Arctic Light/Chrome
CADRU	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FURCA	Fox 36 Performance Elite, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
SOC	Fox Float X Performance Elite, two-position LSC adjust, 185/52.5, custom tuned for Giant

COMPONENTE	
GHIDON	Giant Contact SL TR35, alloy, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
PIPA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIJA SA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SA	Giant Romero SL
PEDALE	N/A

SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM AXS Pod, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	SRAM GX Eagle AXS, T-Type
FRANE	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
MANETE FRANA	Shimano Deore XT BL-M8100
PINIOANE	SRAM GX, T-Type, 10x52
LANT	SRAM GX, T-Type
ANGRENAJ	SRAM GX, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, Press Fit

ROTI	
JANTE	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
BUTUCI	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
SPITE	Sapim, 28, straight pull, DBL Technology
ANVELOPE	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GEOMETRIE

CADRU	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Seat Tube Length (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Seat Tube Angle	76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°			76,8° 77,2° 77,5°		
Top Tube Length (mm)	571 570 569			602 601 600			624 623 622			657 656 655		
Head Tube Length (mm)	100			105			115			125		
Head Tube Angle	64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°			64,4° 64,8° 65,1°		
Fork Rake (mm)	44			44			44			44		
Trail (mm)	134,1 131,3 128,4			134 131,3 128,5			133,9 131,3 128,5			133,9 131,3 128,5		
Wheelbase (mm)	1190 1190 1189			1222 1222 1221			1246 1246 1245			1281 1280 1279		
Chain Stay Length (mm)	440 439 438			440 439 438			440 439 438			440 439 438		
Bottom Bracket Drop (mm)	40 35 30			40 35 30			40 35 30			40 35 30		
Stack (mm)	617 614 611			621 619 616			631 628 625			640 637 634		
Reach (mm)	426 430 434			456 460 464			476 480 484			507 510 513		
Stand Over Height (mm)	733 737 742			737 741 746			754 759 763			752 757 761		
Handlebar Width (mm)	800			800			800			800		
Stem Length (mm)	40			40			50			50		
Crank Length (mm)	165			170			170			170		
Wheel Size	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Toate specificatiile enumerate se pot schimba fara notificare prealabila.