



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Arctic Light/Chrome
OKVIR	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VILICE	Fox 36 Performance Elite, 150mm, GRIP 2 damper, 15x110 Kabolt X, 44mm offset
AMORTIZER	Fox Float X Performance Elite, two-position LSC adjust, 185/52.5, custom tuned for Giant
KOMPONENTE	
KRMILO	Giant Contact SL TR35, alloy, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDEŽ	Giant Romero SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM AXS Pod, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX Eagle AXS, T-Type
ZAVORE	Shimano Deore XT BR-M8120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	Shimano Deore XT BL-M8100
VERIŽNIK	SRAM GX, T-Type, 10x52
VERIGA	SRAM GX, T-Type
GONILKE Z VERIŽNIKI	SRAM GX, T-Type, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
BOTTOM BRACKET	SRAM DUB, Press Fit

OBROČNIKI	
OBROČI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
PESTA	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
NAPERE	Sapim, 28, straight pull, DBL Technology
PLAŠČI	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GEOMETRIJA

OKVIR	S	M	L	XL
	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH	LOW MID HIGH
Dolžina sedežne cevi (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	280	305	330	355
Kot sedežne cevi	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°	76,8° 77,2° 77,5°
Top Tube Length (mm)	571 570 569	602 601 600	624 623 622	646 645 644
Višina glave okvirja (mm)	100	105	115	120
Krmilni kot	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°	64,4° 64,8° 65,1°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	134,1 131,3 128,4	134 131,3 128,5	133,9 131,3 128,5	133,9 131,3 128,5
Medosna razdalja (mm)	1190 1190 1189	1222 1222 1221	1246 1246 1245	1268 1268 1267
Dolžina cevi ob verigi (mm)	440 439 438	440 439 438	440 439 438	440 439 438
Bottom Bracket Drop (mm)	40 35 30	40 35 30	40 35 30	40 35 30
Oddaljenost zgornje cevi od gonilne osi (mm)	617 614 611	621 619 616	631 628 625	641 638 635
Doseg (mm)	426 430 434	456 460 464	476 480 484	496 500 504
Višina zgornje cevi (mm)	733 737 742	737 741 746	754 759 763	774 779 783
Širina krmila (mm)	800	800	800	800
Dolžina opore krmila (mm)	40	40	50	50
Dolžina gonilke (mm)	165	170	170	170
Velikost obročnikov	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]	[F] 29" [R]

Vse navedene specifikacije se lahko spremenijo brez obvestila.