

TRANCE X ADVANCED 1



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Abyss Teal
OKVIR	Advanced-grade composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
VILICE	Fox 36 Float Factory, 150mm, GRIP X damper, 15x110 Kabolt X, 44mm offset
AMORTIZER	Fox Float X Factory, two-position LSC adjust, 185/52.5
KOMPONENTE	
KRMILO	Giant Contact SL TR35, alloy, 780x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single Lock-On, 132x35mm
OPORA KRMILA	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
OPORA SEDEŽA	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SEDEŽ	Giant Romero SL
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM AXS Pod, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM GX AXS Transmission
ZAVORE	TRP EVO Pro, hydraulic, four piston, TRP rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	TRP EVO Pro
VERIŽNIK	SRAM GX, T-Type, 10x52
VERIGA	SRAM GX, T-Type
GONILKE Z VERIŽNIKI	SRAM GX, T-Type, 30t, 55mm chainline S:165mm, M:165mm, L:165mm, XL:165mm
BOTTOM BRACKET	SRAM DUB, Press Fit

OBROČNIKI	
OBROČI	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
PESTA	[F] Giant MTB alloy, 6-bolt [R] Giant MTB alloy, 72 POE (Points of Engagement), 6-bolt, XD driver body
NAPERE	Sapim, 28, straight pull, DBL Technology
PLAŠČI	[F] Maxxis Assegai, 29x2.5 WT, 60 tpi, MaxxTerra, EXO, TR [R] Maxxis DHR II 29x2.4 WT, 60 tpi, MaxxTerra, TR, tubeless
DODATKI	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GEOMETRIJA

OKVIR	S			M			L		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Dolžina sedežne cevi (mm)	400			425			450		
Seat Post Insertion Depth (mm)	280			305			330		
Kot sedežne cevi	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°	76,8°	77,2°	77,5°
Top Tube Length (mm)	571	570	569	602	601	600	624	623	622
Višina glave okvirja (mm)	100			105			115		
Krmilni kot	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°	64,4°	64,8°	65,1°
Zamik vpetja osi (mm)	44			44			44		
Trail (mm)	134,1	131,3	128,4	134	131,3	128,5	133,9	131,3	128,5
Medosna razdalja (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245
Dolžina cevi ob verigi (mm)	440	439	438	440	439	438	440	439	438
Bottom Bracket Drop (mm)	40	35	30	40	35	30	40	35	30
Oddaljenost zgornje cevi od gonilne osi (mm)	617	614	611	621	619	616	631	628	625
Doseg (mm)	426	430	434	456	460	464	476	480	484
Višina zgornje cevi (mm)	733	737	742	737	741	746	754	759	763
Širina krmila (mm)	800			800			800		
Dolžina opore krmila (mm)	40			40			50		
Dolžina gonilke (mm)	165			170			170		

Vse navedene specifikacije se lahko spremenijo brez obvestila.